

### Overview

HP PCM Plus Network Management is a Microsoft® Windows®-based network management platform that enables mapping, configuration, and monitoring. HP PCM Plus provides security and extensibility for small to large networks with remote sites. Network-wide management control allows users to securely add, customize, and restrict network management access. With HP security and wireless solutions, as well as extended third-party support, HP PCM Plus offers a single-pane management solution. With remote agent extensibility, the software can manage many remote sites with encrypted communications and firewall traversal. Customers will gain superior return on management, security, choice, and flexibility.

### Key features

- Unified management across entire network
- Configuring, updating, monitoring, troubleshooting
- Policy-based and multidevice management
- Proactive alert setting, automatic action taking
- Advanced traffic-monitoring capabilities

### Models

HP PCM+ v3 Software with 50-Device License	J9174A
HP PCM+ v3 50-Device License Upgrade	J9173A
HP PCM+ v3 Additional 100-Device License	J9175A
HP PCM+ v3 Unlimited-Device Upgrade License	J9176A
HP PCM+ v3 Software with Unlimited-Device License	J9177A

### Features and Benefits

#### Manageability

- **NEW Improved device monitoring:** the Device Availability report can be used to track and document device and network availability over time or to troubleshoot problem devices; an Alert History graph displays a clear visual display of alerts on the network over time, enabling more proactive responses to network problems
- **NEW Endpoint awareness and VoIP device tracking:** a device map view clearly displays which endpoints are directly connected to the device, including phones, cameras, PCs, and authenticated users; provide real-time location and inventory reporting for VoIP phones, including network details such as VLAN assignment, QoS setting, and PoE status
- **NEW Script Wizard:** allows customers or service providers to securely extend the HP PCM Plus capabilities with custom scripts; the Script Wizard handles device authentication and interactions, making the scripts secure and easier to create
- **NEW HP ONE module management:** simplifies the deployment of HP ONE modules and applications; HP PCM Plus discovers HP ONE modules, and a wizard assists users through the installation and activation of HP ONE applications
- **Functional-based profile settings:** allow network administrators to create new profiles and associate what type of information is available for those functions, providing more control of network access; profiles can be set at a global or regional level to give fine-grained permissions within the network, delivering more secure access to the network at all support levels
- **Cisco device support:** allows Cisco customers to migrate to HP networking products and retain their investments in legacy Cisco switches; provides visibility into device support for Cisco premium switches; with HP PCM Plus and its single pane of management, customers can help isolate network problems in a mixed environment

#### Security

- **Agent security with SSL:** deploying agents in remote environments enables the agent to securely transverse firewalls via a Secure Sockets Layer (SSL) connection to the HP PCM Plus server; once the system is connected, traffic monitoring and event notification use the SSL tunnel to securely transverse the Internet to the destination IP address of the HP PCM Plus server and



### Overview

agent

- **RADIUS authentication of network management administrators:** HP PCM Plus can be configured to use the RADIUS industry-standard protocol to authenticate network management administrators; this approach provides simplified and standardized user administration

### Traffic monitoring

- **In-depth traffic analysis:** an integrated traffic-monitoring interface shows detailed information on traffic throughout the network and delivers minute-by-minute views of the volume and content of traffic at specified points within the network; using enhanced traffic analysis protocols such as XRMON and sFlow, users can monitor input and output traffic levels by device (up to 10,000 polled ports per agent) in order to help network managers enhance network resources

### Integration

- **HP NNMi integration:**
  - **Advanced HP networking device management:** can be integrated with HP NNMi to provide advanced HP networking device support alongside this industry-leading multivendor management platform, which now provides integrated support for most HP networking devices
  - **Distributed deployment:** HP PCM Plus and NNM-i run on separate management servers for increased performance and coordinate management data and actions via secure communications
- **HP Network Node Manager integration:** optional integration with HP Network Node Manager (NNM) v7.5 is available; when integrated with NNM, HP PCM Plus shares NNM's discovery data and provides additional functionality for HP networking devices

### Policy management

- **Policy creation and enforcement:** HP PCM Plus can create policies, set alerts, and take action to enforce network or device policies; network threats, bandwidth, or link problems can be mitigated by proactive policies and can be enforced with alerts and actions

### Additional information

- **NEW Increased platform support:** the HP PCM Plus management server runs on the latest Windows platforms, including Windows Server 2008 R2 and Windows Server 2008 (32-bit and 64-bit versions), and supports Windows 7 for the HP PCM Plus client; HP PCM Plus is also supported on virtual servers: Microsoft Hyper-V, VMware ESX v4, and VMware ESX v3.5
- **Event alerting and analysis:** includes event access and filtering capabilities that allow users to view, acknowledge, and sort network events; a summary displays device as well as HP PCM Plus application events and categorizes them by severity, making it easier to track where bottlenecks and problems exist in the network
- **Backup and restore utility:** provides HP PCM Plus with the ability to back up the net management database and the configuration files of HP PCM Plus; users never have to worry about losing known good configurations or database information when making changes or updates to the network
- **Multiple device firmware updates:** automatically obtains new device firmware from HP and updates devices, allowing users to download the latest version or choose the desired version for downloading; network administrators can schedule firmware updates on one or more groups of devices via the easy-to-use Firmware Update Wizard
- **Configurable Integration Platform (CIP) Wizard:** CIP capabilities are still present in HP PCM Plus, but the CIP Wizard makes integration of third-party network devices, user-defined devices, and applications to HP PCM Plus a snap; the CIP Wizard provides a step-by-step intuitive interface for integrating different vendor devices and applications into HP PCM Plus

### Product Architecture

- **Agent-based architecture:**
  - **User-defined domains:** enable a broad range of activities
  - **Security:** agents traverse firewalls to forward local network information to the server; using one server and up to 25



### Overview

- agents, management becomes faster, more secure, and more compliant with encrypted management communications
- **Scalability:** cost-efficient scalability allows users to pay for management as they need it

### Warranty and support

- **Electronic and telephone support:** limited electronic and telephone support is available from HP; to reach our support centers, refer to [www.hp.com/networking/contact-support](http://www.hp.com/networking/contact-support); for details on the duration of support provided with your product purchase, refer to [www.hp.com/networking/warrantysummary](http://www.hp.com/networking/warrantysummary)
- **Software releases:** to find software for your product, refer to [www.hp.com/networking/support](http://www.hp.com/networking/support); for details on the software releases available with your product purchase, refer to [www.hp.com/networking/warrantysummary](http://www.hp.com/networking/warrantysummary)



### Technical Specifications

HP PCM+ v3 Software with 50-Device License (J9174A)	For networks having up to 50 managed devices, HP recommends the following:	
	Minimum system hardware	2 GB RAM memory 60 GB storage 1000 MB NIC For HP PCM Plus 3.0 as a standalone application with one agent on the server, assuming a dedicated server
	Recommended system hardware	3.0 GHz Intel® Xeon® or Intel® Core™ 2 Duo processor or equivalent processor 2 GB RAM memory 120 GB storage 1000 MB NIC For HP PCM Plus 3.0, assuming a dedicated server with one agent on the server and including HP IDM, MM, and NIM
	Recommended software	Microsoft® Windows® XP Professional SP2/SP3 Microsoft® Windows® Server 2003 Enterprise Edition SP2 (32-bit) Microsoft® Windows® Server 2008 (32-bit or 64-bit) Standard or Enterprise Edition Microsoft® Windows® Server 2008 R2 (64-bit) Standard or Enterprise Edition
	Maximum ports simultaneously monitored per server	10,000
	Maximum sFlow sampling ports per server	3,000
	Maximum polling ports per server	7,000
	Browsers	Microsoft Internet Explorer 6.0 or later
	Required platforms	
	Supported platforms	VMware ESX v3.5 HP Network Node Manager 7.5 HP Network Node Manager-i v8.10 VMware ESX v4 Microsoft Hyper-V
Features	Device autodiscovery Topology and mapping Usable troubleshooting data and alerts Device configuration and management Customizable and executable policies across groups Multiple device configuration management and archiving Creation and configuration of VLANs across the network Traffic monitoring and analysis Email/Pager alerts SNMP trap forwarding OpenView NNM integration Application of policies by user identity	
Notes	Additional processing power may be necessary for extensive traffic monitoring. Some degradation in performance may be expected the greater the number of devices attached to the network.	



### Technical Specifications

Specifications are subject to change.

- Supports up to 2000 devices managed by a single server. For networks with more than 2000 devices, one or more remote agents are required.
- For networks with more than 1500 devices, HP recommends that all agents be remote from the HP PCM server.
- Systems utilizing VMware are limited to networks with 1200 or fewer devices.
- Minimum system requirements for agent: 3.0 GHz Intel Xeon or Intel Core 2 Duo or equivalent processor, 2 GB of memory, 20 GB of hard disk drive space, and capable of running either Microsoft Windows XP (SP2/SP3) or Windows Server 2003 Enterprise Edition (32-bit).
- Minimum system requirements for client: 3.0 GHz Intel Xeon or Intel Core 2 Duo or equivalent processor, 2 GB of memory, 20 GB of hard disk drive space, and capable of running either Microsoft Windows XP (SP2/SP3) or Windows Vista® (Business or Ultimate).

#### Services

3-Year, 9x5 SW phone support, software updates (UQ116E)  
3-year, 24x7 SW phone support, software updates (UQ117E)

Refer to the HP website at [www.hp.com/networking/services](http://www.hp.com/networking/services) for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local HP sales office.

#### HP PCM+ v3 50-Device License Upgrade (J9173A)

For networks having up to 50 managed devices, HP recommends the following:

##### Minimum system hardware

3.0 GHz Intel® Xeon® or Intel® Core™ 2 Duo processor or equivalent processor  
2 GB RAM memory  
60 GB storage  
1000 MB NIC  
For HP PCM Plus 3.0 as a standalone application with one agent on the server, assuming a dedicated server

##### Recommended system hardware

3.0 GHz Intel® Xeon® or Intel® Core™ 2 Duo processor or equivalent processor  
2 GB RAM memory  
120 GB storage  
1000 MB NIC  
For HP PCM Plus 3.0, assuming a dedicated server with one agent on the server and including HP IDM, MM, and NIM on the same server

##### Recommended software

Microsoft® Windows® XP Professional SP2/SP3  
Microsoft® Windows® Server 2003 Enterprise Edition SP2 (32-bit)  
Microsoft® Windows® Server 2008 (32-bit or 64-bit) Standard or Enterprise Edition  
Microsoft® Windows® Server 2008 R2 (64-bit) Standard or Enterprise Edition

##### Maximum ports simultaneously monitored per server

10,000



### Technical Specifications

Maximum sFlow sampling ports per server	3,000
Maximum polling ports per server	7,000
Browsers	Microsoft Internet Explorer 6.0 or later
Required platforms	HP PCM Plus 2.0 or later
Supported platforms	VMware ESX v3.5 HP Network Node Manager 7.5 HP Network Node Manager-i v8.10 VMware ESX v4 Microsoft Hyper-V
Features	Device autodiscovery Topology and mapping Usable troubleshooting data and alerts Device configuration and management Customizable and executable policies across groups Multiple device configuration management and archiving Creation and configuration of VLANs across the network Traffic monitoring and analysis Email/Pager alerts SNMP trap forwarding OpenView NNM integration Application of policies by user identity
Notes	Additional processing power may be necessary for extensive traffic monitoring. Some degradation in performance may be expected the greater the number of devices attached to the network.  Specifications are subject to change. <ul style="list-style-type: none"><li>● Supports up to 2000 devices managed by a single server. For networks with more than 2000 devices, one or more remote agents are required.</li><li>● For networks with more than 1200 devices, HP recommends that all agents be remote from the HP PCM server.</li><li>● Systems utilizing VMware are limited to networks with 1200 or fewer devices.</li><li>● Minimum system requirements for agent: 3.0 GHz Intel Xeon or Intel Core 2 Duo or equivalent processor, 2 GB of memory, 20 GB of hard disk drive space, and capable of running either Microsoft Windows XP (SP2/SP3) or Windows Server 2003 Enterprise Edition (32-bit).</li><li>● Minimum system requirements for client: 3.0 GHz Intel Xeon or Intel Core 2 Duo or equivalent processor, 2 GB of memory, 20 GB of hard disk drive space, and capable of running either Microsoft Windows XP (SP2/SP3) or Windows Vista® (Business or Ultimate).</li></ul>
Services	3-Year, 9x5 SW phone support, software updates (UQ114E) 3-year, 24x7 SW phone support, software updates (UQ115E)

Refer to the HP website at [www.hp.com/networking/services](http://www.hp.com/networking/services) for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local HP sales office.



### Technical Specifications

HP PCM+ v3 Additional 100-Device License (J9175A)	For networks having 50 to 350 managed devices, HP recommends the following:	
	<b>Minimum system hardware</b>	3.0 GHz Intel® Xeon® or Intel® Core™ 2 Duo processor or equivalent processor 2 GB RAM memory 60 GB storage 1000 MB NIC For HP PCM Plus 3.0 as a standalone application with one agent on the server, assuming a dedicated server
	<b>Recommended system hardware</b>	3.0 GHz Intel® Xeon® or Intel® Core™ 2 Duo processor or equivalent processor 3 GB RAM memory 120 GB storage 1000 MB NIC For HP PCM Plus 3.0, assuming a dedicated server with one agent on the server and including HP IDM, MM, and NIM on the same server
	<b>Recommended software</b>	Microsoft® Windows® XP Professional SP2/SP3 Microsoft® Windows® Server 2003 Enterprise Edition SP2 (32-bit) Microsoft® Windows® Server 2008 (32-bit or 64-bit) Standard or Enterprise Edition Microsoft® Windows® Server 2008 R2 (64-bit) Standard or Enterprise Edition
	<b>Maximum ports simultaneously monitored per server</b>	10,000
	<b>Maximum sFlow sampling ports per server</b>	3,000
	<b>Maximum polling ports per server</b>	7,000
	<b>Browsers</b>	Microsoft Internet Explorer 6.0 or later
	<b>Required platforms</b>	HP PCM 3.0
	<b>Supported platforms</b>	VMware ESX v3.5 HP Network Node Manager 7.5 HP Network Node Manager-i v8.10 VMware ESX v4 Microsoft Hyper-V
<b>Features</b>	Device autodiscovery Topology and mapping Usable troubleshooting data and alerts Device configuration and management Customizable and executable policies across groups Multiple device configuration management and archiving Creation and configuration of VLANs across the network Traffic monitoring and analysis Email/Pager alerts SNMP trap forwarding OpenView NNM integration Application of policies by user identity	



### Technical Specifications

#### Notes

Additional processing power may be necessary for extensive traffic monitoring. Some degradation in performance may be expected the greater the number of devices attached to the network.

Specifications are subject to change.

- Supports up to 2000 devices managed by a single server. For networks with more than 2000 devices, one or more remote agents are required.
- For networks with more than 1200 devices, HP recommends that all agents be remote from the HP PCM server.
- Systems utilizing VMware are limited to networks with 1200 or fewer devices.
- Minimum system requirements for agent: 3.0 GHz Intel Xeon or Intel Core 2 Duo or equivalent processor, 2 GB of memory, 20 GB of hard disk drive space, and capable of running either Microsoft Windows XP (SP2/SP3) or Windows Server 2003 Enterprise Edition (32-bit).
- Minimum system requirements for client: 3.0 GHz Intel Xeon or Intel Core 2 Duo or equivalent processor, 2 GB of memory, 20 GB of hard disk drive space, and capable of running either Microsoft Windows XP (SP2/SP3) or Windows Vista® (Business or Ultimate).
- J9175A has the ability to scale up to 3500 devices and 25 agents. Please see J9177A for additional specification recommendations.

#### Services

3-Year, 9x5 SW phone support, software updates (UQ118E)  
3-year, 24x7 SW phone support, software updates (UQ119E)

Refer to the HP website at [www.hp.com/networking/services](http://www.hp.com/networking/services) for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local HP sales office.

#### HP PCM+ v3 Unlimited-Device Upgrade License (J9176A)

For networks having 1200 to 2400 managed devices, HP recommends the following:

##### Minimum system hardware

3.0 GHz Intel® Xeon® or Intel® Core™ 2 Quad processor or equivalent processor  
4 GB RAM memory  
60 GB storage  
1000 MB NIC

For HP PCM Plus 3.0 as a standalone application with one agent on the server, assuming a dedicated server

##### Recommended system hardware

3.0 GHz Intel® Xeon® or Intel® Core™ 2 Quad processor or equivalent processor  
6 GB RAM memory  
120 GB storage  
1000 MB NIC

For HP PCM Plus 3.0, assuming a dedicated server with one agent on the server and including HP IDM, MM, and NIM on the same server





### Technical Specifications

<b>Recommended software</b>	Microsoft® Windows® Server 2003 Enterprise Edition SP2 (32-bit) Microsoft® Windows® Server 2008 (32-bit or 64-bit) Standard or Enterprise Edition Microsoft® Windows® Server 2008 R2 (64-bit) Standard or Enterprise Edition
<b>Maximum ports simultaneously monitored per server</b>	10,000
<b>Maximum sFlow sampling ports per server</b>	3,000
<b>Maximum polling ports per server</b>	7,000
<b>Browsers</b>	Microsoft Internet Explorer 6.0 or later
<b>Required platforms</b>	HP PCM Plus 2.0 or later
<b>Supported platforms</b>	VMware ESX v3.5 HP Network Node Manager 7.5 HP Network Node Manager-i v8.10 VMware ESX v4 Microsoft Hyper-V
<b>Features</b>	Device autodiscovery Topology and mapping Usable troubleshooting data and alerts Device configuration and management Customizable and executable policies across groups Multiple device configuration management and archiving Creation and configuration of VLANs across the network Traffic monitoring and analysis Email/Pager alerts SNMP trap forwarding OpenView NNM integration Application of policies by user identity
<b>Notes</b>	Additional processing power may be necessary for extensive traffic monitoring. Some degradation in performance may be expected the greater the number of devices attached to the network.

Specifications are subject to change.

- Supports up to 2000 devices managed by a single server. For networks with more than 2000 devices, one or more remote agents are required.
- For networks with more than 1200 devices, HP recommends that all agents be remote from the HP PCM server.
- Systems utilizing VMware are limited to networks with 1200 or fewer devices.
- Minimum system requirements for agent: 3.0 GHz Intel Xeon or Intel Core 2 Duo or equivalent processor, 2 GB of memory, 20 GB of hard disk drive space, and capable of running either Microsoft Windows XP (SP2/SP3) or Windows Server 2003 Enterprise Edition (32-bit).
- Minimum system requirements for client: 3.0 GHz Intel Xeon or Intel Core 2 Duo or equivalent processor, 2 GB of memory, 20 GB of hard



### Technical Specifications

	disk drive space, and capable of running either Microsoft Windows XP (SP2/SP3) or Windows Vista® (Business or Ultimate).
<b>Services</b>	3-Year, 9x5 SW phone support, software updates (UQ130E) 3-year, 24x7 SW phone support, software updates (UQ131E)
	Refer to the HP website at <a href="http://www.hp.com/networking/services">www.hp.com/networking/services</a> for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local HP sales office.

#### HP PCM+ v3 Software with Unlimited-Device License (J9177A)

For networks having 1200 to 2400 managed devices, HP recommends the following:

<b>Minimum system hardware</b>	3.0 GHz Intel® Xeon® or Intel® Core™ 2 Quad processor or equivalent processor 4 GB RAM memory 60 GB storage 1000 MB NIC For HP PCM Plus 3.0 as a standalone application with one agent on the server, assuming a dedicated server
<b>Recommended system hardware</b>	3.0 GHz Intel® Xeon® or Intel® Core™ 2 Duo processor or equivalent processor 6 GB RAM memory 120 GB storage 1000 MB NIC For HP PCM Plus 3.0, assuming a dedicated server with one agent on the server and including HP IDM, MM, and NIM on the same server
<b>Recommended software</b>	Microsoft® Windows® Server 2003 Enterprise Edition SP2 (32-bit) Microsoft® Windows® Server 2008 (32-bit or 64-bit) Standard or Enterprise Edition Microsoft® Windows® Server 2008 R2 (64-bit) Standard or Enterprise Edition
<b>Maximum ports simultaneously monitored per server</b>	10,000
<b>Maximum sFlow sampling ports per server</b>	3,000
<b>Maximum polling ports per server</b>	7,000
<b>Browsers</b>	Microsoft Internet Explorer 6.0 or later
<b>Required platforms</b>	
<b>Supported platforms</b>	VMware ESX v3.5 HP Network Node Manager 7.5 HP Network Node Manager-i v8.10 VMware ESX v4 Microsoft Hyper-V
<b>Features</b>	Device autodiscovery Topology and mapping Usable troubleshooting data and alerts Device configuration and management



### Technical Specifications

	<p>Customizable and executable policies across groups Multiple device configuration management and archiving Creation and configuration of VLANs across the network Traffic monitoring and analysis Email/Pager alerts SNMP trap forwarding OpenView NNM integration Application of policies by user identity</p>
<b>Notes</b>	<p>Additional processing power may be necessary for extensive traffic monitoring. Some degradation in performance may be expected the greater the number of devices attached to the network.</p> <p>Specifications are subject to change.</p> <ul style="list-style-type: none"><li>• Supports up to 2000 devices managed by a single server. For networks with more than 2000 devices, one or more remote agents are required.</li><li>• For networks with more than 1200 devices, HP recommends that all agents be remote from the HP server.</li><li>• Systems utilizing VMware are limited to networks with 1200 or fewer devices.</li><li>• Minimum system requirements for agent: 3.0 GHz Intel Xeon or Intel Core 2 Duo or equivalent processor, 2 GB of memory, 20 GB of hard disk drive space, and capable of running either Microsoft Windows XP (SP2/SP3) or Windows Server 2003 Enterprise Edition (32-bit).</li><li>• Minimum system requirements for client: 3.0 GHz Intel Xeon or Intel Core 2 Duo or equivalent processor, 2 GB of memory, 20 GB of hard disk drive space, and capable of running either Microsoft Windows XP (SP2/SP3) or Windows Vista® (Business or Ultimate).</li></ul>
<b>Services</b>	<p>3-year, 24x7 SW phone support, software updates (UQ599E) 3-Year, 9x5 SW phone support, software updates (UQ598E)</p> <p>Refer to the HP website at <a href="http://www.hp.com/networking/services">www.hp.com/networking/services</a> for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local HP sales office.</p>



### Accessories

HP PCM Plus v3 Network Management Software Series	HP Identity Driven Manager 3.0 Software--500-User License	J9438A
	HP Identity Driven Manager 3.0 Software--Additional 1,000-User License	J9440A
	HP Identity Driven Manager 3.0 Software--Unlimited-User License	J9439A
	HP Mobility Manager v3 Software with 50-Device License	J9291A
	HP Mobility Manager v3 Additional 100-Device License	J9292A
	HP Mobility Manager v3 Software with Unlimited-Device License	J9293A
	HP PCM+ Identity Driven Manager v4 Software Module with 500-user License	J9752A
	HP PCM+ Identity Driven Manager v4 Software Module with Unlimited-user License	J9753A
	HP PCM+ Identity Driven Manager v4 additional 1000-user License	J9754A



### Accessory Product Details

**NOTE:** Details are not available for all accessories. The following specifications were available at the time of publication.

<b>HP Identity Driven Manager 3.0 Software--500-User License (J9438A)</b>	<b>Identity Driven Manager 3.0 software and license for managing up to 500 users.</b>
<b>RADIUS server support</b>	Microsoft Network Policy Server on Windows Server 2008 (32-bit) Microsoft Internet Authentication Service (IAS) on Windows Server 2003 (32-bit) FreeRADIUS supplied with Red Hat Enterprise Linux (4.7 and 5.2) RADIUS on the Network Access Controller 800 FreeRADIUS supplied with SuSE Linux Enterprise Server (9.3 and 10.2)
<b>Features</b>	Intuitive Explorer-style interface OpenView NNM integration Application of policies by user identity <ul style="list-style-type: none"><li>● Auto VLAN assignment</li><li>● Auto set quality of service by user</li><li>● Auto set bandwidth assignment by user</li></ul> Rule-based access rights deployment Dynamic rights assignment based on: <ul style="list-style-type: none"><li>● Time</li><li>● Location</li><li>● User system</li></ul> Auto-discovery of: <ul style="list-style-type: none"><li>● RADIUS servers</li><li>● Realms</li><li>● Users</li></ul>
<b>Notes</b>	Additional specifications <ul style="list-style-type: none"><li>● Supports environments with up to 10,000 users.</li><li>● Supports up to 10 RADIUS servers with HP Identity Driven Manager agents installed.</li></ul> Requires the HP PCM Plus 3.0 or greater network management platform. <ul style="list-style-type: none"><li>● Please see HP PCM Plus 3.0 for hardware and software system requirements.</li></ul>
<b>Services</b>	3-Year, 9x5 SW phone support, software updates (UQ124E) 3-year, 24x7 SW phone support, software updates (UQ125E)  Refer to the HP website at <a href="http://www.hp.com/networking/services">www.hp.com/networking/services</a> for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local HP sales office.



### Accessory Product Details

HP Identity Driven Manager 3.0 Software-- Additional 1,000-User License (J9440A)	License to add support for managing an additional 1,000 users with the Identity Driven Manager 3.0 product.
	<b>RADIUS server support</b> —
	<b>Features</b> —
	<b>Notes</b> Additional specifications <ul style="list-style-type: none"><li>● Supports environments with up to 10,000 users.</li><li>● Supports up to 10 RADIUS servers with HP Identity Driven Manager agents installed.</li></ul> Requires the HP PCM Plus 3.0 or greater network management platform. <ul style="list-style-type: none"><li>● Please see HP PCM Plus 3.0 for hardware and software system requirements. Requires the HP Identity Driven Manager 3.0 base product (J9438A).</li></ul> Multiple licenses for additional 1,000 users can be added to the base HP Identity Driven Manager product to support larger numbers of users.
	<b>Services</b> 3-year, 24x7 SW phone support, software updates (UQ119E) 3-Year, 9x5 SW phone support, software updates (UQ118E)  Refer to the HP website at <a href="http://www.hp.com/networking/services">www.hp.com/networking/services</a> for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local HP sales office.

HP Identity Driven Manager 3.0 Software-- Unlimited-User License (J9439A)	Identity Driven Manager 3.0 software and license for managing an unlimited number of users.
	<b>RADIUS server support</b> Microsoft Network Policy Server on Windows Server 2008 (32-bit) Microsoft Internet Authentication Service (IAS) on Windows Server 2003 (32-bit) FreeRADIUS supplied with Red Hat Enterprise Linux (4.7 and 5.2) RADIUS on the Network Access Controller 800 FreeRADIUS supplied with SuSE Linux Enterprise Server (9.3 and 10.2)
	<b>Features</b> Intuitive Explorer-style interface OpenView NNM integration Application of policies by user identity <ul style="list-style-type: none"><li>● Auto VLAN assignment</li><li>● Auto set quality of service by user</li><li>● Auto set bandwidth assignment by user</li></ul> Rule-based access rights deployment  Dynamic rights assignment based on: <ul style="list-style-type: none"><li>● Time</li><li>● Location</li><li>● User system</li></ul>



### Accessory Product Details

	Auto-discovery of:
	<ul style="list-style-type: none"><li>● RADIUS servers</li><li>● Realms</li><li>● Users</li></ul>
Notes	Additional specifications
	<ul style="list-style-type: none"><li>● Supports environments with up to 10,000 users.</li><li>● Supports up to 10 RADIUS servers with HP Identity Driven Manager agents installed.</li></ul>
	Requires the HP PCM Plus 3.0 or greater network management platform.
	Please see HP PCM Plus 3.0 for hardware and software system requirements.
Services	3-year, 24x7 SW phone support, software updates (UQ133E) 3-Year, 9x5 SW phone support, software updates (UQ132E)
	Refer to the HP website at <a href="http://www.hp.com/networking/services">www.hp.com/networking/services</a> for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local HP sales office.

---

**HP Mobility Manager v3 Software with 50-Device License (J9291A)** Notes

	For system requirements, please refer to the Manager specifications list. Supports all HP MultiService Mobility controllers and access points except MSM313, MSM313R, MSM323 and MSM323R. Does not support RF Security Sensor MSM415.
	HP Mobility Manager v3 requires HP Manager Plus 3.0 or later. For more licensing information, refer to the HP Network Management License Guide. For a current list of supported mobility devices, refer to the HP Mobility Manager Supported Devices matrix document.
	HP Mobility Manager v3 supports all HP MultiService Mobility (MSM) controllers and access points except MSM313, MSM313R, MSM323, MSM323R, and the MSM415 RF security sensor.
Services	3-Year, 9x5 SW phone support, software updates (UQ116E) 3-year, 24x7 SW phone support, software updates (UQ117E)
	Refer to the HP website at: <a href="http://www.hp.com/networking/services">www.hp.com/networking/services</a> for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local HP sales office.



### Accessory Product Details

**HP Mobility Manager v3  
Additional 100-Device  
License  
(J9292A)**

**Services**

For system requirements, please refer to the Manager specifications list. Supports all HP MultiService Mobility controllers and access points except MSM313, MSM313R, MSM323 and MSM323R. Does not support RF Security Sensor MSM415. Requires HP Mobility Manager v3 software with 50 Device License (J9291A). For more licensing information, refer to the HP Network Management License Guide. For a list of supported mobility devices, see the HP Mobility Manager Supported Devices matrix document. HP Mobility Manager supports all HP MultiService Mobility controllers and access points except MSM313, MSM313R, MSM323, MSM323R, and the MSM415 RF security sensor.

3-Year, 9x5 SW phone support, software updates (UQ120E)  
3-year, 24x7 SW phone support, software updates (UQ121E)

Refer to the HP website at: [www.hp.com/networking/services](http://www.hp.com/networking/services) for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local HP sales office.

---

**HP Mobility Manager v3  
Software with Unlimited-  
Device License  
(J9293A)**

**Services**

For system requirements, please refer to the Manager specifications list. Supports all HP MultiService Mobility controllers and access points except MSM313, MSM313R, MSM323 and MSM323R. Does not support RF Security Sensor MSM415. Requires HP PCM+ 3.20 or later platform. For more licensing information, refer to the HP Network Management License Guide. "Unlimited-device license" means that HP does not impose a limit on the number of devices attached to the network as a condition of the license. HP Mobility Manager manages all HP MultiService Mobility controllers and access points except MSM313, MSM313R, MSM323, MSM323R, and the MSM415 RF security sensor.

3-Year, 9x5 SW phone support, software updates (UQ132E)  
3-year, 24x7 SW phone support, software updates (UQ133E)

Refer to the HP website at: [www.hp.com/networking/services](http://www.hp.com/networking/services) for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local HP sales office.

---





### Accessory Product Details

HP PCM+ Identity Driven Manager v4 Software Module with 500-user License (J9752A) Identity Driven Manager v4 software and license for managing up to 500 users

#### Features

Intuitive Explorer-style interface  
OpenView NNM integration  
Application of policies by user identity

- Auto VLAN assignment
- Auto set quality of service by user
- Auto set bandwidth assignment by user

Rule-based access rights deployment  
Dynamic rights assignment based on:

- Time
- Location
- User system

Auto-discovery of:

- RADIUS servers
- Realms
- Users

#### Notes

Additional specifications:

- Supports environments with up to 20,000 users
- Supports up to 10 RADIUS servers with HP Identity Driven Manager agents installed

Requires the HP PCM Plus v4 or later network management platform

- Please see HP PCM+ v4 for hardware and software system requirements.

#### Services

Refer to the HP website at: [www.hp.com/networking/services](http://www.hp.com/networking/services) for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local HP sales office.

HP PCM+ Identity Driven Manager v4 Software Module with Unlimited-user License (J9753A) Identity Driven Manager v4 software and license for managing an unlimited number of users

#### Features

Intuitive Explorer-style interface  
OpenView NNM integration  
Application of policies by user identity

- Auto VLAN assignment
- Auto set quality of service by user
- Auto set bandwidth assignment by user

Rule-based access rights deployment  
Dynamic rights assignment based on:

- Time
- Location
- User system

Auto-discovery of:

- RADIUS servers
- Realms
- Users

#### Notes

Additional specifications:



### Accessory Product Details

- Supports environments with up to 20,000 users
- Supports up to 10 RADIUS servers with HP Identity Driven Manager agents installed

Requires the HP PCM Plus v4 or later network management platform

- Please see HP PCM+ v4 for hardware and software system requirements.

### Services

Refer to the HP website at: [www.hp.com/networking/services](http://www.hp.com/networking/services) for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local HP sales office.

To learn more, visit [www.hp.com/networking](http://www.hp.com/networking)

© Copyright 2007, 2009-2011 Hewlett-Packard Development Company, L.P. The information contained herein is subject to change without notice. The only warranties for HP products and services are set forth in the express warranty statements accompanying such products and services. Nothing herein should be construed as constituting an additional warranty. HP shall not be liable for technical or editorial errors or omissions contained herein.

Intel, Intel Core, and Intel Xeon are trademarks of Intel Corporation in the U.S. and other countries. Microsoft, Windows, and Windows Vista are U.S. registered trademarks of Microsoft Corporation.

