

Overview

Models

HP E-M110 Access Point US

J9385B

HP E-M110 Access Point WW

J9388B

Key features

- Entry-level access point
- Single radio
- IEEE 802.11a/b/g
- Autonomous mode
- Two external antennas

Product overview

HP E-M110 Access Point is an entry-level, single IEEE 802.11a/b/g radio device that can be configured to operate as an access point, a wireless distribution system (WDS) bridge, or a full-spectrum IEEE 802.11 wireless LAN (WLAN) monitor. The E-M110 Access Point supports up to two Virtual Service Communities, each with independent VLAN and wireless security profiles. It is plenum-rated and powered by an IEEE 802.3af(PoE)source. The M110 access point is Wi-Fi Certified for WPA2, WPA, and WEP security and has hardware-assisted AES and RC4 encryption.

Features and benefits

Quality of Service (QoS)

- **IEEE 802.1p prioritization:** delivers data to devices based on the priority and type of traffic
- **Diagnostic:**
 - Client event log records association, authentication, and DHCP events
 - Packet capture tool for Ethernet and IEEE 802.11 interfaces (PCAP format)
 - Data rate matrix
- **RF management:**
 - Automatically selects channel on power-up and continuously improves channel selection based on background interference scan
 - Configurable background rogue scanning
 - Automatically adjusts transmit power to reduce interference
- **Network management:** SNMP v2c, SNMP v3, MIB-II with Traps, and RADIUS Authentication Client MIB (RFC 2618) Embedded HTML management tool with secure access (SSL and VPN) Scheduled configuration and firmware upgrades from central server

Connectivity

- **Auto-MDIX:** automatically adjusts for straight-through or crossover cables on all 10/100 ports
- **IEEE 802.3af Power over Ethernet (PoE) support:** simplifies deployment and dramatically reduces installation costs by helping to eliminate the time and cost involved in supplying local power at each access point location

Mobility

- **Interoperability:** Wi-Fi Alliance certifications, including IEEE 802.11g Wi-Fi and WPA2 to help ensure multivendor interoperability



Overview

- **Virtual Service Communities (VSCs):**
 - Up to 2 SSIDs, each with a unique MAC address, and configurable SSID broadcasts
 - Individual security profiles per VSC
 - Configurable DTIM and minimum data rate per VSC
 - Each VSC mapped to separate IEEE 802.1Q VLANs
 - WMM and/or WMM-PS
 - Security filter
 - IP filter
- **AP client access control functions:**
 - IEEE 802.1X authentication using EAP-SIM, EAP-FAST, EAP-TLS, EAP-TTLS, and PEAP
 - MAC address authentication using local or RADIUS access lists
 - RADIUS AAA using EAP-MD5, PAP, CHAP, and MS-CHAPv2
 - RADIUS Client (RFC 2865 and 2866) with location-aware support
 - Layer 2 wireless client isolation
- **Enhanced Security:**
 - Configurable Ethernet MAC and protocol filters
 - WPA2, WPA, and WEP
 - IEEE 802.1X PEAP WLAN authentication
 - Hardware-assisted AES and RC4 encryption
- **Location flexibility:**
 - 100 mW radio and antenna diversity provide excellent range
 - Configurable IEEE 802.11 a/b/g radio with external antenna connectors
 - Plenum rated
 - Centrally manageable

Security

- **Choice of IEEE 802.11i, Wi-Fi Protected Access 2 (WPA2), or WPA:** locks out unauthorized wireless access by authenticating users prior to granting network access; robust Advanced Encryption Standard (AES) or Temporal Key Integrity Protocol (TKIP) encryption secures the data integrity of wireless traffic
- **Local wireless bridge client traffic filtering:** when enabled, prevents communication between wireless devices associated with the same access point
- **IEEE 802.1X:** provides port-based user authentication with support for Extensible Authentication Protocol (EAP) MD5, TLS, TTLS, and PEAP with choice of AES, TKIP, and static or dynamic WEP encryption for protecting wireless traffic between authenticated clients and the access point

Warranty and support

- **Lifetime warranty:** for as long as you own the product with advance replacement and next-business-day delivery (available in most countries)*
- **Electronic and telephone support:** limited electronic and telephone support is available from HP; refer to: www.hp.com/networking/warranty for details on the support provided and the period during which support is available
- **Software releases:** refer to: www.hp.com/networking/warranty for details on the software releases provided and the period during which software releases are available for your product(s)

* Hardware warranty replacement for as long as you own the product, with next business day advance replacement (available in most countries) with a five-year hardware warranty replacement for the disk drive included with HP AllianceONE Services zl Module, HP Threat Management Services zl Module, HP PCM+ Agent with AllianceONE Services zl Module, and HP E-MSM765 zl Mobility Controller. For details, refer to the HP Software License, Warranty, and Support booklet at: www.hp.com/networking/warranty.



Technical Specifications

HP E-M110 Access Point US (J9385B)

Ports	1 RJ-45 autosensing 10/100 port (IEEE 802.3 Type 10BASE-T, IEEE 802.3u Type 100BASE-TX); Duplex: half or full	
AP characteristics	Radios	Single (a/b/g)
	Radio operation modes	Client access
	AP operation modes	Autonomous
	Wi-Fi Alliance Certification	a/b/g Wi-Fi Certified
Physical characteristics	Dimensions	5(d) x 5.5(w) x 1.3(h) in. (12.7 x 13.97 x 3.3 cm)
	Weight	2.0 lb. (0.91 kg)
	Enclosure	Indoor, plenum rated
Environment	Operating temperature	32°F to 122°F (0°C to 50°C)
	Operating relative humidity	5% to 95%, noncondensing
	Nonoperating/Storage temperature	-40°F to 176°F (-40°C to 80°C)
	Nonoperating/Storage relative humidity	5% to 95%, noncondensing
Electrical characteristics	Shock and vibration	EN61373
	Description	IEEE 802.3af PoE compliant or 5 VDC from available AC power supply
	Maximum power rating	5 W
	Antenna connector	(2) RP-SMA with diversity
	Antenna	(2) 2 dBi dual-band 2.4/5 GHz
Frequency band and operating channels	Number of external antennas	2
	FCC	2.412 - 2.462 GHz (1-11 channels)
		5.180 - 5.240 GHz (36-48 channels)
		5.745 - 5.825 GHz (149-165 channels)
	EN	2.412 - 2.472 GHz (1-13 channels)
5.180 - 5.240 GHz (36-48 channels)		
Radio	FCC Part 15.247; FCC Part 15.407 (US)	
Safety	UL 2043; UL 60950-1; IEC 60950-1; EN 60950-1; CAN/CSA-C22.2 No. 60950-1	
Emissions	EN 55022 Class B; EN 301 489-1; EN 301 489-17; ICES-003 Class B; FCC Part 15, Class B	
RF Exposure	FCC Bulletin OET-65C; RSS-102; EN 50385	
Notes	Maximum transmit power varies by country.	
Services	3-year, 4-hour onsite, 13x5 coverage for hardware (UN691E)	
	3-year, 4-hour onsite, 24x7 coverage for hardware (UN692E)	
	3-year, 4-hour onsite, 24x7 coverage for hardware, 24x7 software phone support (UN694E)	
	3-year, 24x7 SW phone support, software updates (UN693E)	
	4-year, 4-hour onsite, 13x5 coverage for hardware (US029E)	
	4-year, 4-hour onsite, 24x7 coverage for hardware (US030E)	
	4-year, 4-hour onsite, 24x7 coverage for hardware, 24x7 software phone (US031E)	
	4-year, 24x7 SW phone support, software updates (US032E)	
5-year, 4-hour onsite, 13x5 coverage for hardware (US033E)		



Technical Specifications

- 5-year, 4-hour onsite, 24x7 coverage for hardware (US034E)
- 5-year, 4-hour onsite, 24x7 coverage for hardware, 24x7 software phone (US035E)
- 5-year, 24x7 SW phone support, software updates (US036E)
- 3 Yr 6 hr Call-to-Repair Onsite (UW422E)
- 4 Yr 6 hr Call-to-Repair Onsite (UW423E)
- 5 Yr 6 hr Call-to-Repair Onsite (UW424E)

Refer to the HP website at: www.hp.com/networking/services for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local HP sales office.

Radio characteristics: IEEE 802.11a

Data rate	6 Mbps	54 Mbps
Receiver sensitivity	-90 dBm	-72 dBm
Transmit power	20 dBm	16 dBm

Radio characteristics: IEEE 802.11b

Data rate	1 Mbps	11 Mbps
Receiver sensitivity	-90 dBm	-90 dBm
Transmit power	20 dBm	20 dBm

Radio characteristics: IEEE 802.11g

Data rate	6 Mbps	54 Mbps
Receiver sensitivity	-92 dBm	-72 dBm
Transmit power	20 dBm	16 dBm

Standards and protocols Mobility

(applies to all products in series)

- IEEE 802.11a High Speed Physical Layer in the 5 GHz Band
- IEEE 802.11b Higher-Speed Physical Layer Extension in the 2.4 GHz Band
- IEEE 802.11g Further Higher Data Rate Extension in the 2.4 GHz Band
- IEEE 802.11i Medium Access Control (MAC) Security Enhancements

HP E-M110 Access Point WW (J9388B)

Ports	1 RJ-45 autosensing 10/100 port (IEEE 802.3 Type 10BASE-T, IEEE 802.3u Type 100BASE-TX); Duplex: half or full	
AP characteristics	Radios	Single (a/b/g)
	Radio operation modes	Client access
	AP operation modes	Autonomous
	Wi-Fi Alliance Certification	a/b/g Wi-Fi Certified
Physical characteristics	Dimensions	5(d) x 5.5(w) x 1.3(h) in. (12.7 x 13.97 x 3.3 cm)
	Weight	2.0 lb. (0.91 kg)
	Enclosure	Indoor, plenum rated
Environment	Operating temperature	32°F to 122°F (0°C to 50°C)
	Operating relative humidity	5% to 95%, noncondensing
	Nonoperating/Storage temperature	-40°F to 176°F (-40°C to 80°C)



Technical Specifications

	Nonoperating/Storage relative humidity	5% to 95%, noncondensing
	Shock and vibration	EN61373
Electrical characteristics	Description	IEEE 802.3af PoE compliant or 5 VDC from available AC power supply
	Maximum power rating	5 W
	Antenna connector	(2) RP-SMA with diversity
	Antenna	(2) 2 dBi dual-band 2.4/5 GHz
	Number of external antennas	2
Frequency band and operating channels	FCC	2.412 - 2.462 GHz (1-11 channels) 5.180 - 5.240 GHz (36-48 channels) 5.745 - 5.825 GHz (149-165 channels)
	EN	2.412 - 2.472 GHz (1-13 channels) 5.180 - 5.240 GHz (36-48 channels)
Radio	FCC Part 15.247; FCC Part 15.407 (US); RSS-210 (Canada); EN 300 328; ARIB STD-T66; IDA Registration (Singapore); MIC approval (Korea); RCR STD-33; ARIB STD-T71 (Japan); EN 301 893 (EU)	
Safety	UL 2043; UL 60950-1; IEC 60950-1; EN 60950-1; CAN/CSA-C22.2 No. 60950-1	
Emissions	EN 55022 Class B; EN 301 489-1; EN 301 489-17; ICES-003 Class B; FCC Part 15, Class B	
RF Exposure	FCC Bulletin OET-65C; RSS-102; EN 50385	
Notes	Maximum transmit power varies by country.	
Services	3-year, 4-hour onsite, 13x5 coverage for hardware (UN691E) 3-year, 4-hour onsite, 24x7 coverage for hardware (UN692E) 3-year, 4-hour onsite, 24x7 coverage for hardware, 24x7 software phone support (UN694E) 3-year, 24x7 SW phone support, software updates (UN693E) 4-year, 4-hour onsite, 13x5 coverage for hardware (US029E) 4-year, 4-hour onsite, 24x7 coverage for hardware (US030E) 4-year, 4-hour onsite, 24x7 coverage for hardware, 24x7 software phone (US031E) 4-year, 24x7 SW phone support, software updates (US032E) 5-year, 4-hour onsite, 13x5 coverage for hardware (US033E) 5-year, 4-hour onsite, 24x7 coverage for hardware (US034E) 5-year, 4-hour onsite, 24x7 coverage for hardware, 24x7 software phone (US035E) 5-year, 24x7 SW phone support, software updates (US036E) 3 Yr 6 hr Call-to-Repair Onsite (UW422E) 4 Yr 6 hr Call-to-Repair Onsite (UW423E) 5 Yr 6 hr Call-to-Repair Onsite (UW424E)	

Refer to the HP website at: www.hp.com/networking/services for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local HP sales office.



Technical Specifications

Radio characteristics: IEEE 802.11a

Data rate	6 Mbps	54 Mbps
Receiver sensitivity	-90 dBm	-72 dBm
Transmit power	20 dBm	16 dBm

Radio characteristics: IEEE 802.11b

Data rate	1 Mbps	11 Mbps
Receiver sensitivity	-90 dBm	-90 dBm
Transmit power	20 dBm	20 dBm

Radio characteristics: IEEE 802.11g

Data rate	6 Mbps	54 Mbps
Receiver sensitivity	-92 dBm	-72 dBm
Transmit power	20 dBm	16 dBm

Standards and protocols

(applies to all products in series)

Mobility

- IEEE 802.11a High Speed Physical Layer in the 5 GHz Band
- IEEE 802.11b Higher-Speed Physical Layer Extension in the 2.4 GHz Band
- IEEE 802.11g Further Higher Data Rate Extension in the 2.4 GHz Band
- IEEE 802.11i Medium Access Control (MAC) Security Enhancements



Accessories

HP E-M110 Access Point Series accessories	Power Supply	
	HP E-MSM31x and E-MSM32x Power Supply	J9405B
	HP E-MSM31x and E-MSM32x Power Supply	J9405A
	HP 1-Port Power Injector	J9407A
	External Antenna	
	HP 5 dBi @2.4GHz Indoor/Outdoor Omnidir Antenna	J8441A
	HP 8 dBi @ 2.4GHz Outdoor Omnidirectional Antenna	J8444A
	HP 3 dBi Dual-Band Diversity Antenna	J8997A
	HP 7 dBi Dual-Band Directional Antenna	J8999A

To learn more, visit: www.hp.com/networking

© Copyright 2011 Hewlett-Packard Development Company, L.P. The information contained herein is subject to change without notice. The only warranties for HP products and services are set forth in the express warranty statements accompanying such products and services. Nothing herein should be construed as constituting an additional warranty. HP shall not be liable for technical or editorial errors or omissions contained herein.

