


## Overview

### HP ProBook 440 G1 Notebook PC



#### Front/Left

- |  |                                       |
|--|---------------------------------------|
| 1. WWAN antennas (2)* (select models only) | 11. Media Card Reader                 |
| 2. WLAN antennas**                         | 12. Hard drive activity LED indicator |
| 3. Dual-array microphone***                | 13. USB 3.0 ports (2)                 |
| 4. Webcam light***                         | 14. HDMI port                         |
| 5. Webcam (select model models only)       | 15. RJ-45 (network) jack              |
| 6. Wireless on/off button                  | 16. VGA monitor port                  |
| 7. Speaker mute button                     | 17. Power connector                   |
| 8. Optional Fingerprint Reader             | 18. Power button                      |
| 9. Touchpad pick buttons                   | 19. Speakers (2)                      |
| 10. Touchpad                               |                                       |

\* The antennas are not visible from the outside of the computer. For optimal transmission, keep the areas immediately around the antennas free from obstructions.

\*\* The number of WLAN antennas in the displays is determined by the WLAN selected

\*\*\* Feature is available with select models with webcam configuration.


# QuickSpecs

HP ProBook 440 G1 Notebook PC

HP ProBook 450 G1 Notebook PC


HP ProBook 470 G1 Notebook PC

## Overview



### Right

1. Audio-out (headphone) jack
2. Audio-in (microphone) jack
3. USB 2.0 ports (2)
4. Optical drive (select models only)
5. Optical drive eject button (select models only)
6. Security lock slot



### Bottom

1. Battery and service door release latches
2. Battery bay
3. Vents
4. Service door


## HP ProBook 450 G1 Notebook PC



# QuickSpecs

HP ProBook 440 G1 Notebook PC  
HP ProBook 450 G1 Notebook PC  
HP ProBook 470 G1 Notebook PC

## Overview



### Front/Left

- |  |                                       |
|--|---------------------------------------|
| 1. WWAN antennas (2)* (select models only) | 11. Media Card Reader                 |
| 2. WLAN antennas**                         | 12. Hard drive activity LED indicator |
| 3. Dual-array microphone ***               | 13. USB 3.0 ports (2)                 |
| 4. Webcam light***                         | 14. HDMI port                         |
| 5. Webcam (select model models only)       | 15. RJ-45 (network) jack              |
| 6. Wireless on/off button                  | 15. RJ-45 (network) lights (2)        |
| 7. Speaker mute button                     | 16. VGA monitor port                  |
| 8. Optional Fingerprint Reader             | 17. Power connector                   |
| 9. Touchpad pick buttons                   | 18. Power button                      |
| 10. Touchpad                               | 19. Speakers (2)                      |

\* The antennas are not visible from the outside of the computer. For optimal transmission, keep the areas immediately around the antennas free from obstructions.

\*\* The number of WLAN antennas in the displays is determined by the WLAN selected.

\*\*\* Feature is available with select models with webcam configuration.


# QuickSpecs

HP ProBook 440 G1 Notebook PC

HP ProBook 450 G1 Notebook PC


HP ProBook 470 G1 Notebook PC

## Overview



### Right

1. Audio-out (headphone) jack
2. Audio-in (microphone) jack
3. USB 2.0 ports (2)
4. Optical drive (select models only)
5. Optical drive eject button (select models only)
6. Security lock slot




### Bottom

1. Battery and service door release latches
2. Battery bay
3. Vents
4. Service door



## Overview

### HP ProBook 470 G1 Notebook PC



#### Front/Left

- |                                |  |
|--------------------------------|--|
| 1. WLAN antennas*              | 10. Media Card Reader                                  |
| 2. Dual-array microphone       | 11. Hard drive activity LED indicator                  |
| 3. Webcam light                | 12. USB 3.0 ports (2)                                  |
| 4. Webcam (select models only) | 13. HDMI port  |
| 5. Wireless on/off button      | 14. RJ-45 (network) jack<br>RJ-45 (network) lights (2) |
| 6. Speaker mute button         | 15. VGA monitor port                                   |
| 7. Optional Fingerprint Reader | 16. Power connector                                    |
| 8. Touchpad pick buttons       | 17. Power button                                       |
| 9. Touchpad                    | 18. Speakers (2)                                       |

\* The number of WLAN antennas in the displays is determined by the WLAN selected.


# QuickSpecs

HP ProBook 440 G1 Notebook PC

HP ProBook 450 G1 Notebook PC

HP ProBook 470 G1 Notebook PC

## Overview




1. Audio-out (headphone) jack
2. Audio-in (microphone) jack
3. USB 2.0 ports (2)

### Right

4. Optical drive (select models only)
5. Optical drive eject button (select models only)
6. Security lock slot

## Overview



### Bottom

- 1. Battery and service door release latches
- 2. Battery bay
- 3. Vents
- 4. Service door

## Overview

### At A Glance

- Windows 8.1 versions, Windows 8, Windows 7 versions, SUSE Linux, or FreeDOS
- Aluminum reinforced chassis with multi-layer soft touch paint that keep system looking good longer
- Full-sized spill-resistant keyboard; full separate numeric keypad (HP ProBook 450 and 470 only)
- Larger Touchpad with gestures support, on/off button with LED indicator
- Enhanced security features including HP Client Security and optional HP Fingerprint Reader
- Optional HD webcam with dual-microphone array for video conferencing\*
- HDMI port for connecting to high-resolution displays; USB 3.0 ports
- DTS Sound+ optimized for high fidelity audio
- Widescreen LED-backlit HD display with 16:9 aspect ratio with available 17.3-inch diagonal HD+ (HP ProBook 470), 15.6-inch diagonal HD, 15.6-inch diagonal HD with Touch option (HP ProBook 450), 14-inch diagonal HD (HP ProBook 440)
- Choice of 4th generation Intel® Core™ i7, i5 and i3 processors, Intel Celeron and Pentium processor
- Wireless on/off and speaker mute buttons for convenient management of the connectivity and speaker.
- Flexible wireless connectivity options:
  - Integrated HP Mobile Broadband Module (HP ProBook 440 G1 and 450 G1 selective models)
  - Integrated 802.11 b/g/n wireless LAN module
  - Integrated 802.11 a/b/g/n/AC, a/b/g/n or b/g/n with Bluetooth 4.0 combo card

\* Optional on models with integrated graphics only.

**NOTE: See important legal disclosures for all listed specs in their respective features sections.**



## Features

### PRODUCT NAMES

HP ProBook 440 G1 Notebook PC  
HP ProBook 450 G1 Notebook PC  
HP ProBook 470 G1 Notebook PC

### OPERATING SYSTEM

#### Preinstalled

Windows 8.1 Pro 64\*  
Windows 7 Professional (available through downgrade rights from Windows 8.1 Pro)\*\*  
Windows 8.1 64\*  
Windows 8 Pro 64\*  
Windows 7 Professional (available through downgrade rights from Windows 8 Pro)\*\*  
Windows 8 64\*  
Windows 7 Professional 64\*\*\*  
Windows 7 Home Premium 64\*\*\*  
Windows 7 Home Basic 64\*\*\*  
SUSE Linux Enterprise Desktop 11  
FreeDOS

\* Not all features are available in all editions of Windows 8/8.1. Systems may require upgraded and/or separately purchased hardware, drivers and/or software to take full advantage of Windows 8/8.1 functionality. See <http://www.microsoft.com> for details.

\*\* This system is preinstalled with Windows® 7 Pro software and also comes with a license and media for Windows 8 Pro software. You may only use one version of the Windows software at a time. Switching between versions will require you to uninstall one version and install the other version. You must back up all data (files, photos, etc.) before uninstalling and installing operating systems to avoid loss of your data.

\*\*\* Not all features are available in all editions of Windows 7. This system may require upgraded and/or separately purchased hardware to take full advantage of Windows 7 functionality. See <http://www.microsoft.com/windows/windows-7/> for details.

### PROCESSOR

4<sup>th</sup> Generation Intel® Core™ i7-4702MQ (2.2GHz, 6MB L3 cache, 4 cores)  
Up to 3.2GHz with Intel Turbo Boost Technology  
4<sup>th</sup> Generation Intel® Core™ i5-4200M (2.5GHz, 3MB L3 cache, 2 cores)  
Up to 3.1GHz with Intel Turbo Boost Technology  
4<sup>th</sup> Generation Intel® Core™ i3-4100M (2.5GHz, 3MB L3 cache, 2 cores)  
4<sup>th</sup> Generation Intel® Core™ i3-4000M (2.4GHz, 3MB L3 cache, 2 cores)  
Intel® Pentium 3550M (2.3GHz, 2MB L3 cache, 2 cores)  
Intel® Celeron 2950M (2.0GHz, 2MB L3 cache, 2 cores)

\* Multi-Core is designed to improve performance of certain software products. Not all customers or software applications will necessarily benefit from use of this technology. 64-bit computing on Intel® architecture requires a computer system with a processor, chipset, BIOS, operating system, device drivers, and applications enabled for Intel® 64 architecture. Processors will not operate (including 32-bit operation) without an Intel® 64 architecture-enabled BIOS. Performance will vary depending on your hardware and software configurations. Intel's numbering is not a measurement of higher performance.

**NOTE:** Processor speed denotes maximum performance mode; processors will run at lower speeds in battery optimization mode.

## Features

### CHIPSET

Mobile Intel® HM87 Express

### GRAPHICS

Integrated\*:

Intel HD\*\* Graphics 4600 (4th Generation Intel Quad-Core i7 and Dual-Core i5 and i3)

Intel HD\*\* Graphics (Celeron and Pentium configurations)

Switchable Discrete:

AMD Radeon™ HD\*\* 8750M, with 1 or 2 GB dedicated DDR3 video memory\*\*\*

\* HP ProBook 440 and 450 only. HP ProBook 470 supports switchable discrete graphics only.

\*\* HD content required to view HD images.

\*\*\* AMD Dynamic Switchable Graphics technology requires either an AMD "A" series APU or an Intel processor, plus an AMD Radeon™ discrete graphics configuration and is not available on FreeDOS and Linux OS. With AMD Dynamic Switchable Graphics technology, full enablement of all discrete graphics video and display features may not be supported on all systems (e.g. OpenGL applications will run on the integrated GPU or the APU as the case may be).

### DISPLAY

#### HP ProBook 440 G1

##### Internal

14" diagonal LED-backlit HD anti-glare (1366 x 768)

##### External

Up to 32-bit per pixel color depth

##### VGA

Port supports resolutions up to 1920 x 1080 external resolution @60 Hz

##### HDMI

Supports direct connection to high-definition displays with up to 1920 x 1200@60Hz resolution and 7-channel audio with one convenient cable (not included)

**NOTE:** HD content required to view HD images.

**NOTE:** Resolutions are dependent upon monitor capability, and resolution and color depth settings.

#### HP ProBook 450 G1

##### Internal

15.6" diagonal LED-backlit HD Touch Display is shatter, scratch, and smudge resistant (1366 x 768)

15.6" diagonal LED-backlit HD anti-glare (1366 x 768)

##### External

Up to 32-bit per pixel color depth

##### VGA

Port supports resolutions up to 1920 x 1080 external resolution @60 Hz

##### HDMI

Supports direct connection to high-definition displays with up to 1920 x 1200@60Hz resolution and 7-channel audio with one convenient cable (not included)

**NOTE:** HD content required to view HD images.

## Features

**NOTE:** Resolutions are dependent upon monitor capability, and resolution and color depth settings.

### HP ProBook 470 G1

#### Internal

17.3" diagonal LED-backlit HD+ anti-glare (1600 x 900)

#### External

Up to 32-bit per pixel color depth

#### VGA

Port supports resolutions up to 1920 x 1080 external resolution @60 Hz

#### HDMI

Supports direct connection to high-definition displays with up to 1920 x 1200@60Hz resolution and 7-channel audio with one convenient cable (not included)

**NOTE:** HD content required to view HD images.

**NOTE:** Resolutions are dependent upon monitor capability, and resolution and color depth settings.

## STORAGE AND DRIVES

### Primary Storage Bay

#### Hard Drives

320/500/750 GB\*\*/1 TB\*\* 5400 rpm SMART SATA II HDD;

500 GB\*\* 7200 rpm SMART SATA II HDD

750GB\*\* 7200 rpm SMART SATA II HDD (available on 450 G1 only)

500 GB\*\* 5400 rpm SMART SATA II Hybrid HDD/SSHD

#### Solid State Drive\*

128 GB\*\* 2.5" Solid State Drive

### HP 3D DriveGuard (Windows only)

The hard drive is mounted directly to the notebook frame, reducing the transmission of shock to the hard drive

\* Available on 450G1 only

\*\*For hard drives and solid state drives, GB = 1 billion bytes. TB = 1 trillion bytes. Actual formatted capacity is less. Up to 16 GB (for Windows 7) and 36 GB (for Windows 8) of system disk is reserved for the system recovery software.

## Features

### OPTICAL DRIVES

#### Fixed 9.5 mm SATA optical drive

Blu-ray ROM DVD+/-RW SuperMulti DL Drive\*†

DVD+/-RW SuperMulti DL Drive\*

DVD-ROM Drive

No optical drive option

\* Sold separately as an optional feature.

† For Blu-ray drives, certain disc, digital connection, compatibility and/or performance issues may arise, and do not constitute defects in the product. Flawless playback on all systems is not guaranteed. In order for some Blu-ray titles to play, they may require an HDMI digital connection and your display may require HDCP support. HD-DVD disks cannot be played on this drive. Note that DVD-RAM cannot read or write to 2.6GB Single Sided/5.2 GB Double Sided - Version 1.0 media. Actual speeds may vary. Don't copy copyright-protected materials. Double Layer discs can store more data than single layer discs; discs burned with this drive may not be compatible with many existing single-layer DVD drives and players.

### MEMORY

#### Standard

DDR3L 1.35V SDRAM (1600 MHz)

Two SODIMM slots supporting dual-channel memory

2 GB, 4 GB, and 8 GB SODIMMs\*

#### Maximum

Upgradeable to 16384 MB with optional 8192 MB SODIMMs in slots 1 and 2

#### Dual-channel

Maximized dual-channel performance requires SODIMMs of the same size and speed in both memory slots.

**NOTE:** Due to the non-industry standard nature of some third-party memory modules, we recommend HP branded memory to ensure compatibility. If you mix memory speeds, the system will perform at the lower memory speed. With Windows Starter 32-bit operating systems, the amount of usable memory is dependent upon your configuration, so that above 3 GB all memory may not be available due to system resource requirements.

### NETWORKING/COMMUNICATIONS

#### Wireless

Support for a broad range of secure, integrated wireless LAN and wireless WAN options featuring support for the latest industry standards. Broadband Wireless (WWAN) requires a Windows operating system and is available in select countries as a standard, factory configurable feature only. Integrated Bluetooth is also available (factory configurable only) and can be combined with any of the supported wireless LAN and wireless WAN options.

#### Broadband Wireless (WWAN) (WWAN and LTE are not available on the HP ProBook 470 G1)

HP hs3110 HSPA+ Mobile Broadband Module\*

HP lt4112 LTE/HSPA+ Gobi 4G Module\*, \*\*

#### Wireless LAN (WLAN)\*\*\*

Realtek 802.11 b/g/n (1x1)\*\*\*

Atheros 802.11 b/g/n (1x1) with Bluetooth® v4.0 combo\*\*\*

Intel Dual Band Wireless-AC 3160 802.11 a/b/g/n/ac (1x1) WiFi with Bluetooth 4.0 combo\*\*\*, \*\*\*\*

Intel Dual Band Wireless-AC 7260AN 802.11 a/b/g/n/ac (2x2) WiFi with Bluetooth 4.0 combo (Non vPro)

Intel Dual Band Wireless-N 7260AN 802.11 a/b/g/n (2x2) WiFi with Bluetooth 4.0 combo\*\*\*

## Features

**NOTE:** Supports Bluetooth® v2.1 on Linux operating systems

\* WWAN is an optional feature sold separately or as an add on feature. WWAN connection requires wireless data service contract, network support, and is not available in all areas. Contact service provider to determine the coverage area and availability. Connection speeds will vary due to location, environment, network conditions, and other factors.

\*\* 4G LTE not available on all products, in all regions and only available on products featuring Intel processors.

\*\*\*Wireless access point and Internet service is required and is not included. Availability of public wireless access points limited.

\*\*\*\* The specifications for the 802.11ac WLAN are draft specifications and are not final. If the final specifications differ from the draft specifications, it may affect the ability of the notebook to communicate with other 802.11ac WLAN devices.

### Communications

Realtek 10/100/1000\* Ethernet Controller

\* The term "10/100/1000" or "Gigabit" Ethernet indicates compatibility with IEEE standard 802.3ab for Gigabit Ethernet, and does not connote actual operating speed of 1 Gb/s. For high-speed transmission, connection to a Gigabit Ethernet server and network infrastructure is required.

## AUDIO/MULTIMEDIA

### Audio

DTS Sound+

Integrated stereo speakers

Integrated digital microphone (dual-microphone array when equipped with optional webcam)

Function keys for microphone mute, volume up, volume down

Stereo headphone/line out

Stereo microphone/line in

### Webcam

Optional\* 720p HD\*\* webcam

- HD format (widescreen)
- Supports videoconferencing (non-HD) and still image capture
- High quality fixed focus lens
- Video capture at various resolutions up to 1280x720 resolution (720p) and up to 30fp
- M-JPEG compression supports higher frame rates for video capture and videoconferencing
- Improved low light sensitivity
- Improved dynamic range
- Skype-ready\*\*

\* Sold separately as an optional feature.

\*\* HD content required to view HD images.

\*\*\* Internet access required.

## Features

### KEYBOARDS/POINTING DEVICES/BUTTONS & FUNCTION KEYS

#### Keyboard

The HP spill-resistant keyboard is designed using a thin layer of Mylar film under the keyboard. The 101/102-key compatible keyboard features a full-pitch key layout with desktop keyboard features, such as editing keys, both left and right control and alt keys, and function keys. US and International key layouts are available. Includes a separate numeric keypad (HP ProBook 450 and 470 only).

#### Pointing Devices

Touchpad with gestures support, on/off button with LED indicator, two-way scroll, two pick buttons

#### Buttons and Function Keys

Separate launch buttons provide easy access to wireless on/off and speaker mute. Function keys provide control of features including: standby mode, display brightness, external display, microphone mute, volume down, and volume up.

### SOFTWARE AND SECURITY

#### Preinstalled Software with Windows Operating System

HP Wireless Hotspot\*

HP Mobile Connect (EMEA Only) (Win 8 Only)\*\*

HP ePrint (HP Exclusive)\*\*\*

HP Hotkey support

HP 3D Driveguard (Windows required)

PDF Complete Corporate Edition\*\*\*\*

Skype ready \*\*\*\*\*

HP Recovery Manager

HP Support Assistant

Buy Office

Intel Wireless Display\*\*\*\*\*

**NOTE:** HP Recovery Manager enables fast recovery of the factory preinstalled image if the system becomes corrupted or if important system files are accidentally deleted. Up to 16 GB (for Windows 7) and 36 GB (for Windows 8) of system disk is reserved for the system recovery software.

\* The wireless hotspot application requires an active internet connection and separately purchased data plan. While HP wireless hotspot is active, on-device applications will continue to work and will use the same data plan as the wireless hotspot. Wireless hotspot data usage may incur additional charges. Check with your service provider for plan details. Requires Windows.

\*\* Internet access required.

\*\*\* Requires an Internet connection to HP web-enabled printer and HP ePrint account registration (for a list of eligible printers, supported documents and image types and other HP ePrint details, see [www.hp.com/go/eprintcenter](http://www.hp.com/go/eprintcenter)). Requires optional broadband module. Broadband use requires separately purchased service contract. Check with service provider for coverage and availability in your area. Separately purchased data plans or usage fees may apply. Print times and connection speeds may vary.

\*\*\*\* PDF Complete Corporate Edition includes 50 PDF creations or six months, whichever comes first. Purchase license afterwards for full functionality.

\*\*\*\*\* Skype-ready. Skype is not offered in China.

\*\*\*\*\* Integrated Intel Wi-Di feature is available on select configurations only and requires separately purchased projector, tv or computer monitor with an integrated or external Wi-Di receiver. External Wi-Di receivers connect to the projector, tv or computer monitor via a standard HDMI cable, also sold separately.

#### Security

##### Standard

HP Client Security (Windows only)

## Features

HP Trust Circles Standard (Available in Fall 2013)  
Microsoft Security Essentials(Windows 7)/Microsoft Defender (Windows 8)\*  
HP Drive Encryption\*\*  
HP BIOS Protection\*\*\*  
Security lock slot  
TPM 1.2 Embedded Security Chip

### Optional

Intel® Anti-Theft (requires a Computrace subscription)\*\*\*\*  
Intel Identity Protection\*\*\*\*\*  
HP Fingerprint reader

**NOTE:** The Absolute Persistence agent is shipped turned off, and must be activated by customers when they purchase a subscription. Subscriptions can be purchased for terms ranging multiple years. Service is limited, check with Absolute for availability outside the U.S.

\* Opt in and internet connection required for updates.

\*\* Requires Windows. Data is protected prior to Drive Encryption login. Turning the PC off or into hibernate logs out of Drive Encryption and prevents data access. Drive encryption planned to be available in October 2013.

\*\*\* HP Tools partition with an HP BIOS required for automatic recovery.

\*\*\*\* Intel Anti-Theft security is supported on Intel Core i processors and requires a separately purchased Absolute Computrace service subscription and must be activated and configured. Check with Absolute for availability in your country. Intel and HP assume no liability for lost or stolen data and/or systems or any other damages resulting therefrom. See

<http://www.intel.com/technology/anti-theft/>.

\*\*\*\*\* Intel Identity Protection feature is only available with Intel Core Processors. Intel® IPT security requires separate Symantec VIP software service subscription and must be activated and configured. Requires a website that uses Symantec VIP Authentication Service and Microsoft® Windows. Intel® and HP assume no liability for lost or stolen data and/or systems or any other damages resulting therefrom.

For more information on HP security solutions refer to: <http://www.hp.com/go/security>.

## POWER

### Power Supply

#### HP ProBook 440 G1 Notebook PC

Models with discrete graphics:

External 90W HP Smart AC Adapter

Models with integrated graphics:

External 65W HP Smart AC Adapter

Power cord included is 3.28-foot (1 meter).

Total length including external AC adapter is 9.38 feet (2.86 meter).

HP Fast Charge\*

#### HP ProBook 450 G1 Notebook PC

Models with discrete graphics:

External 90W HP Smart AC Adapter

Models with integrated graphics:

External 65W HP Smart AC Adapter

Power cord included is 3.28-foot (1 meter).

Total length including external AC adapter is 9.38 feet (2.86 meter).

HP Fast Charge\*

## Features

### HP ProBook 470 G1 Notebook PC

90W HP Smart AC Adapter

Power cord included is 3.28-foot (1 meter).

Total length including external AC adapter is 9.38 feet (2.86 meter).

HP Fast Charge\*

### Primary Battery

HP 9-cell Lithium-Ion Battery (93 WHr)

HP 6-cell Lithium-Ion Battery (47 WHr)

HP 6-cell Long Life Lithium-Ion Battery (51 WHr) - available on 440 G1 only, available in March

### Battery Life with Windows 7

	Configurations with integrated graphics	Configurations with discrete graphics
<b>HP ProBook 440</b>		
9-cell (93 WHr) battery	Up to 17 hours 30 mins	Up to 17 hours 30 mins
6-cell (47 WHr) battery	Up to 9 hours 15 mins	Up to 9 hours
<b>HP ProBook 450</b>		
9-cell (93 WHr) battery	Up to 17 hours 15 mins	Up to 17 hours
6-cell (47 WHr) battery	Up to 9 hours 15 mins	Up to 9 hours
<b>HP ProBook 470</b>		
9-cell (93 WHr) battery	N/A	Up to 15 hours 15 mins
6-cell (47 WHr) battery	N/A	Up to 8 hours 15 mins

### System Standby Time\*

Up to 12 days

\* Windows 7 battery life will vary depending on numerous factors including product model, configuration, loaded applications, features, use, wireless functionality, and power management settings. The maximum capacity of the battery will naturally decrease with time and usage. See [www.bapco.com](http://www.bapco.com) for additional details.

\*\* Standby life will vary depending on various factors including battery, Memory, CPU, EC and LAN chip. The maximum capacity of the battery will naturally decrease with time and usage.

**NOTE:** Fast Charge recharges your battery up to 90% within 90 minutes when the system is off (6-cell only).

### Power Conservation

Supports enhanced Intel SpeedStep technology (allows Battery Optimized Mode, Maximum Performance Mode, or Automatic mode)

AMD PowerPlay technology (discrete models)

Hibernation

Standby

ACPI compliance



## Features

### WEIGHTS & DIMENSIONS

#### HP ProBook 440 G1 Notebook PC

##### Weight

Starting at 4.63 lb (2.10 kg) with optical drive (weight will vary by configuration)

Starting at 4.34 lb (1.97 kg) without optical drive (weight will vary by configuration)

##### Dimensions (w x d x h)

13.35 x 9.38 x 0.88 (front) - 1.12 in (at rear)

33.92 x 23.85 x 2.24 (front) - 2.86 cm (at rear)

#### HP ProBook 450 G1 Notebook PC

##### Weight

Starting at 5.22 lb (2.37 kg) with optical drive without touch (weight will vary by configuration)

Starting at 4.98 lb (2.26 kg) without optical drive without touch (weight will vary by configuration)

Starting at 5.84 lb (2.65 kg) with optical drive with touch (weight will vary by configuration)

Starting at 5.6 lb (2.54 kg) without optical drive with touch (weight will vary by configuration)

##### Dimension (wxdxh)

14.76 x 10.09 x 0.9 (front) - 1.14 in (at rear) (non-Touch)

37.5 x 25.6 x 2.28 (front) - 2.9 cm (at rear) (non-Touch)

14.76 x 10.09 x 0.95 (front) - 1.20 in(at rear) (Touch)

37.5 x 25.6 x 2.42( front) - 3.0 4cm(at rear) (Touch)

#### HP ProBook 470 G1 Notebook PC

##### Weight

Starting at 6.61 lb (3.0 kg) with optical drive (weight will vary by configuration)

Starting at 6.33 lb (2.87 kg) without optical drive (weight will vary by configuration)

##### Dimensions (w x d x h)

16.29 x 11 x 1.00 (front) - 1.24 in (at rear)

41.3 8 x 27.95 x 2.53 (front) - 3.15 cm (at rear)

### PORTS/SLOTS

USB 3.0 – Two

USB 2.0 – Two

HDMI 1.4a – One

Stereo microphone input – One

Headphone/line out – One

RJ-45 (Ethernet) – One

Power connector – One

VGA – One

#### Digital Media Slots

Multi Media Reader Slot supporting SD, SDHC, SDXC, Memory Stick, MSXC

## Features

### SERVICE AND SUPPORT

HP Services offers limited 3-year, 1-year and 90-day warranty options depending on country; 1-year limited warranty on primary battery. On-site service and warranty upgrades are also available. HP Care Pack Services extend service contracts beyond the standard warranties. To choose the right level of service for your HP product, use the HP Care Pack Services Lookup Tool at: <http://www.hp.com/go/lookuptool>. Consult the HP Customer Support Center for details. <http://h20000.www2.hp.com/bizsupport/TechSupport/ProductRoot.jsp>.

**NOTE:** Service levels and response times for HP Care Packs may vary depending on your geographic location. Service starts on date of hardware purchase. Restrictions and limitations apply. For details, visit <http://www.hp.com/go/cpc>.

## Technical Specifications

### SYSTEM UNIT

<b>Stand-Alone Power Requirements (AC Power)</b>	<b>Nominal Operating Voltage</b>	19 V	
	<b>Average Operating Power</b>		
		<b>Windows 7 (64-bit)</b>	<b>Windows 8 (64-bit)</b>
	ProBook 440 Integrated graphics	8.81 W	9.08 W
	ProBook 440 Discrete graphics	9.38 W	9.65 W
	ProBook 450 Integrated graphics	8.8 W	8.7 W
	ProBook 450 Discrete graphics	9.68 W	9.22 W
	ProBook 470 Discrete graphics	9.55 W	9.88 W
	<b>Max Operating Power</b>	Discrete < 90W UMA < 65W	
<b>Temperature</b>	<b>Operating</b>	32° to 95° F (0° to 35° C) (not writing optical) 41° to 95° F (5° to 35° C) (writing optical)	
	<b>Non-operating</b>	-4° to 140° F (-20° to 60° C)	
<b>Relative Humidity</b>	<b>Operating</b>	10% to 90%, non-condensing	
	<b>Non-operating</b>	5% to 95%, 101.6° F (38.7° C) maximum wet bulb temperature	
<b>Shock</b>	<b>Operating</b>	40 G, 2 ms, half-sine	
	<b>Non-operating</b>	200 G, 2 ms, half-sine	
<b>Random Vibration</b>	<b>Operating</b>	0.75 grms	
	<b>Non-operating</b>	1.50 grms	
<b>Altitude (unpressurized)</b>	<b>Operating</b>	-50 to 10,000 ft (-15.24 to 3,048 m)	
	<b>Non-operating</b>	-50 to 40,000 ft (-15.24 to 12,192 m)	
<b>Planned Industry Standard Certifications</b>	<b>UL</b>	Yes	
	<b>CSA</b>	Yes	
	<b>FCC Compliance</b>	Yes	
	<b>ENERGY STAR®</b>	Select models*	
	<b>EPEAT</b>	Registered Gold in United States**	
	<b>ICES</b>	Yes	
	<b>Australia / NZ A-Tick Compliance</b>	Yes	
	<b>CCC</b>	Yes	
	<b>Japan VCCI Compliance</b>	Yes	
	<b>KC</b>	Yes	
	<b>BSMI</b>	Yes	
	<b>CE Marking Compliance</b>	Yes	

## Technical Specifications

<b>BNCI or BELUS</b>	Yes
<b>CIT</b>	Yes
<b>GOST</b>	Yes
<b>Saudi Arabian Compliance (ICCP)</b>	Yes
<b>SABS</b>	Yes
<b>UKRSERTCOMPUTER</b>	Yes

\* Configurations of the HP ProBook 440 G1, HP ProBook 450 G1 and HP ProBook 470 G1 that are ENERGY STAR® qualified are identified as HP ProBook 440 G1 ENERGY STAR, HP ProBook 450 G1 ENERGY STAR and HP ProBook 470 G1 ENERGY STAR on HP websites and on [www.energystar.gov](http://www.energystar.gov).

\*\* EPEAT® registration varies by country. See [www.epeat.net](http://www.epeat.net) for registration status by country. EPEAT status listed above applies to U.S.

For accessibility information on HP products, please visit: <http://www.hp.com/accessibility>.

## DISPLAYS

**14.0-inch LED HD  
(1366 x 768)  
anti-glare**

<b>Dimensions (W x H)</b>	12.63 x 7.39 in (32.09 x 18.76 cm)	
<b>Weight</b>	0.71 lb (320g) (max)	
<b>Diagonal Size</b>	14.0 in (35.6cm)	
<b>Surface Treatment</b>	Anti-glare	
<b>Contrast Ratio</b>	400:1 (min)	
<b>Refresh Rate</b>	60 Hz	
<b>Brightness</b>	200 nit (typical)	
<b>Pixel Resolution</b>	<b>Pitch</b>	0.227 mm
	<b>Format</b>	1366 x 768
	<b>Configuration</b>	RGB Stripe
<b>Backlight</b>	LED	
<b>PPI</b>	112 ppi	
<b>Viewing Angle</b>	±30° Horizontal, ±10° Vertical (minimum) 30/30/20/10 (Left/Right/Down/Up) (minimum) or 45/45/35/25 (Left/Right/Down/Up) (typical)	

## Technical Specifications

<b>15.6-inch LED HD (1366 x 768) with Touch</b>	<b>Dimensions (W x H)</b>	13.54 x 7.64 in (34.39 x 19.41 cm)
	<b>Weight</b>	500g max.
	<b>Diagonal Size</b>	15.6 in (39.6cm)
	<b>Contrast Ratio</b>	300:1 (min)
	<b>Refresh Rate</b>	60 Hz
	<b>Brightness</b>	200 nit (typical)
	<b>Pixel Resolution</b>	<b>Pitch</b> 0.252 x 0.252
		<b>Format</b> 1366 x 768 (HD)
		<b>Configuration</b> 1366 x 768
	<b>Backlight</b>	LED
	<b>PPI</b>	106 ppi
	<b>Viewing Angle</b>	±30° Horizontal, ±10° Vertical (minimum) 30/30/20/10 (Left/Right/Down/Up) (minimum) or 45/45/35/25 (Left/Right/Down/Up) (typical)
	<b>15.6-inch LED HD (1366 x 768) anti-glare</b>	<b>Dimensions (W x H)</b>
<b>Weight</b>		500g max.
<b>Diagonal Size</b>		15.6 in (39.6cm)
<b>Surface Treatment</b>		Anti-glare
<b>Contrast Ratio</b>		400:1 (min)
<b>Refresh Rate</b>		60 Hz
<b>Brightness</b>		200 nit (typical)
<b>Pixel Resolution</b>		<b>Pitch</b> 0.252 mm
		<b>Format</b> 1366 x 768
		<b>Configuration</b> RGB Stripe
<b>Backlight</b>		LED
<b>PPI</b>		106 ppi
<b>Viewing Angle</b>		±30° Horizontal, ±10° Vertical (minimum) 30/30/20/10 (Left/Right/Down/Up) (minimum) or 45/45/35/25 (Left/Right/Down/Up) (typical)

## Technical Specifications

<b>17.3-inch LED HD+ anti-glare</b>	<b>Active Area (W x H)</b>	15.0 x 8.5 in (38.2 x 21.5 cm)
	<b>Weight</b>	570g max.
	<b>Diagonal Size</b>	17.3 in (43.9 cm)
	<b>Surface Treatment</b>	Anti-glare
	<b>Contrast Ratio</b>	400:1 (min)
	<b>Refresh Rate</b>	60 Hz
	<b>Brightness</b>	200 nit (typical)
	<b>Pixel Resolution</b>	<b>Pitch</b> 0.23868 x 0.23868 mm
		<b>Format</b> 1600 x 900
		<b>Configuration</b> RGB Stripe
	<b>Backlight</b>	LED
	<b>PPI</b>	106
	<b>Viewing Angle</b>	±30° Horizontal, ±10° Vertical (minimum) 30/30/20/10 (Left/Right/Down/Up) (minimum) or 45/45/35/25 (Left/Right/Down/Up) (typical)

## STORAGE AND DRIVES

### Internal Storage

<b>500 GB* 7200 rpm SATA Hard Drive</b>	<b>Drive Weight</b>	0.25 lbs (115g)
	<b>Capacity</b>	500 GB
	<b>Height</b>	0.37 in (9.5 mm)
	<b>Width</b>	2.75 in (70 mm)
	<b>Interface</b>	ATA-8, SATA 2.6, 3.0 Gb/s, NCQ
	<b>Transfer Rate</b>	<b>Synchronous</b> (maximum) 300 MB/s (Drive Capability)
	<b>Seek Time</b>	<b>Single Track</b> 1.5 ms
	(typical reads, including settling)	<b>Average</b> 11 ms
		<b>Maximum</b> 22 ms
	<b>Rotational Speed</b>	7200 rpm
	<b>Logical Blocks</b>	976,773,168
<b>Operating Temperature</b>	32° to 140° F (0° to 60° C) [case temp]	
<b>Features</b>	ATA Security	

# QuickSpecs

HP ProBook 440 G1 Notebook PC

HP ProBook 450 G1 Notebook PC

HP ProBook 470 G1 Notebook PC

## Technical Specifications

### 320 GB\* 5400 rpm SATA Hard Drive

<b>Drive Weight</b>	0.25 lbs (115 g)
<b>Capacity</b>	320 GB
<b>Height</b>	0.37 in (9.5 mm)
<b>Width</b>	2.75 in (70 mm)
<b>Interface</b>	ATA-8, SATA 2.6, 3.0 Gb/s, NCQ
<b>Transfer Rate</b>	<b>Synchronous</b> (maximum) 300 MB/s (Drive Capability)
<b>Seek Time</b> (typical reads, including settling)	<b>Single Track</b> 1.5 ms
	<b>Average</b> 11 ms
	<b>Maximum</b> 22 ms
<b>Rotational Speed</b>	7200 rpm
<b>Logical Blocks</b>	625,142,448
<b>Operating Temperature</b>	32° to 140° F (0° to 60° C) [case temp]
<b>Features</b>	ATA Security

### 500 GB\* 5400 rpm SATA Hard Drive

<b>Drive Weight</b>	0.22 lb (101 g)
<b>Capacity</b>	500 GB
<b>Height</b>	0.37 in (9.5 mm)
<b>Width</b>	2.75 in (70 mm)
<b>Interface</b>	ATA-8, SATA 2.6, 3.0 Gb/s, NCQ
<b>Transfer Rate</b>	<b>Synchronous</b> (maximum) 300 MB/s (Drive Capability)
<b>Seek Time</b> (typical reads, including settling)	<b>Single Track</b> 3 ms
	<b>Average</b> 13 ms
	<b>Maximum</b> 24 ms
<b>Rotational Speed</b>	5400 rpm
<b>Logical Blocks</b>	976,773,168
<b>Operating Temperature</b>	32° to 140° F (0° to 60° C) [case temp]
<b>Features</b>	ATA Security



# QuickSpecs

HP ProBook 440 G1 Notebook PC  
HP ProBook 450 G1 Notebook PC  
HP ProBook 470 G1 Notebook PC

## Technical Specifications

### 750 GB\* 5400 rpm SATA Hard Drive

<b>Drive Weight</b>	0.22 lb (101 g)
<b>Capacity</b>	750 GB
<b>Height</b>	0.37 in (9.5 mm)
<b>Width</b>	2.75 in (70 mm)
<b>Interface</b>	ATA-8, SATA 2.6, 3.0 Gb/s, NCQ
<b>Transfer Rate</b>	<b>Synchronous</b> (maximum) 300 MB/s (Drive Capability)
<b>Seek Time</b> (typical reads, including settling)	<b>Single Track</b> 3 ms
	<b>Average</b> 13 ms
	<b>Maximum</b> 24 ms
<b>Rotational Speed</b>	5400 rpm
<b>Logical Blocks</b>	1,465,149,168
<b>Operating Temperature</b>	32° to 140° F (0° to 60° C) [case temp]
<b>Features</b>	ATA Security

### 1 TB\* 5400 rpm SATA Hard Drive

<b>Drive Weight</b>	0.254 lb (115 g)
<b>Capacity</b>	1 TB
<b>Height</b>	0.37 in (9.5 mm)
<b>Width</b>	2.75 in (70 mm)
<b>Interface</b>	ATA-8, SATA 2.6, 3.0 Gb/s, NCQ
<b>Transfer Rate</b>	<b>Synchronous</b> (maximum) 300 MB/s (Drive Capability)
<b>Seek Time</b> (typical reads, including settling)	<b>Single Track</b> 3 ms
	<b>Average</b> 13 ms
	<b>Maximum</b> 24 ms
<b>Rotational Speed</b>	5400 rpm
<b>Logical Blocks</b>	1,953,525,168
<b>Operating Temperature</b>	32° to 140° F (0° to 60° C) [case temp]
<b>Features</b>	ATA Security





# QuickSpecs

HP ProBook 440 G1 Notebook PC  
HP ProBook 450 G1 Notebook PC  
HP ProBook 470 G1 Notebook PC

## Technical Specifications

<b>500 GB* 5400 rpm SMART SATA II Hybrid HDD/SSHD</b>	<b>Drive Weight</b>	0.209 lb (95 g)			
	<b>Capacity</b>	500 GB			
	<b>Height</b>	0.276 in (7 mm)			
	<b>Width</b>	2.76 in (70.1 mm)			
	<b>Interface</b>	ATA-8, SATA 2.6, 6.0 Gb/s, NCQ			
	<b>Transfer Rate</b>	<b>Synchronous (maximum)</b>	600 MB/s (Drive Capability)		
	<b>Seek Time</b> (typical reads, including settling)	<b>Single Track</b>	2 ms		
		<b>Average</b>	12 ms		
		<b>Maximum</b>	NIL ms		
	<b>Rotational Speed</b>	7200 rpm			
	<b>Logical Blocks</b>	976,773,168			
	<b>Operating Temperature</b>	32° to 140° F (0° to 60° C) [case temp]			
	<b>Features</b>	ATA Security			
<b>SATA 6 Gb/s 128 GB*, 2.5- inch Solid State Drive</b>	<b>Drive Weight</b>	73 Grams			
	<b>Capacity</b>	128 GB			
	<b>Height</b>	0.276 in (7 mm)			
	<b>Width</b>	2.76 in (70 mm)			
	<b>Interface</b>	SATA 3 (6 Gb/s)			
	<b>Performance</b>	<b>Maximum Sequential Read</b>	415 MB/s	<b>Maximum Sequential Write</b>	175 MB/s
		<b>Logical Blocks</b>	250,069,680		
	<b>Operating Temperature</b>	32° to 158°F (0° to 70°C) [case temp]			
	<b>Features</b>	ATA Security; ATA-8; SATA 3.0; DIPM; TRIM			

\* For hard drives and solid state drives, GB = 1 billion bytes. TB = 1 trillion bytes. Actual formatted capacity is less. Up to 16 GB (for Windows 7) and 36 GB (for Windows 8) of system disk is reserved for the system recovery software.

## Optical Drives



## Technical Specifications

<b>DVD+/-RW SuperMulti DL Drive</b>	<b>Access Times</b>	Random	<140ms CD (typical) < 160 ms DVD (typical)
	<b>Max Data Transfer Rate</b>	24X CD-ROM 8X DVD 24X CD-R 24X CD-RW 8X DVD+R 8X DVD+RW 8X DVD-R 6X DVD-RW 6X - DVD+R Dual Layer 6X - DVD-R Dual Layer 5X DVD-RAM	
	<b>Transfer Mode</b>	UDMA Mode 5	
	<b>Interface</b>	Gen 1 SATA	
	<b>Supported Media (read)</b>	CD-DA, CD-TEXT, CD-ROM, CD-ROM XA, MIXED MODE CD, CD-I, CD-I Bridge (Photo-CD, Video CD), Multisession CD (Photo-CD, CD-EXTRA, Portfolio, CD-R, CD-RW), CD-R, CD-RW, DVD-ROM (DVD-5, DVD-9, DVD-10, DVD-18), DVD-R, DVD-RW, DVD+R, DVD+RW, DVD-RAM	
	<b>Supported Media (write)</b>	CD-R, CD-RW, DVD+R, DVD+RW, DVD-R, DVD-RW, DVD-RAM, DVD+R DL, DVD-R DL	
	<b>Max Media Capacity (read)</b>	8.5 GB	
	<b>Max Media Capacity (write)</b>	8.5 GB	
	<b>Transport</b>	Tray Loading	
	<b>Blu-ray ROM DVD+/-RW SuperMulti DL Drive</b>	<b>Access Times</b>	Random
<b>Max Data Transfer Rate</b>		24X CD-ROM 8X DVD-ROM 24X CD-R 16X CD-RW 8X DVD+R 8X DVD+RW 8X DVD-R 6X DVD-RW 4X - DVD+R Dual Layer 4X - DVD-R Dual Layer 5X DVD-RAM 6X BD-ROM	
<b>Transfer Mode</b>		UDMA Mode 5	
<b>Interface</b>		Gen 1 SATA	
<b>Supported Media (read)</b>		CD-DA, , CD-TEXT, CD-ROM, CD-ROM XA, MIXED MODE CD, CD-I, CD-I Bridge (Photo-CD, Video CD), Multisession CD (Photo-CD, CD-EXTRA, Portfolio, CD-R, CD-RW), CD-R, CD-RW, DVD-ROM (DVD-5, DVD-9, DVD-10, DVD-18), DVD-R, DVD-RW, DVD+R, DVD+RW. DVD-RAM, BD-ROM, BD-R, BD-RE	

## Technical Specifications

<b>Supported Media</b> (write)	CD-R, CD-RW, DVD+R, DVD+R DL, DVD+RW, DVD-R, DVD-R DL, DVD-RW, DVD-RAM
<b>Max Media Capacity</b> (read)	50.0 GB
<b>Max Media Capacity</b> (write)	8.5 GB
<b>Transport</b>	Tray Loading

## SECURITY

<b>HP Fingerprint Reader</b> (optional)	<b>Mobile Voltage Operation</b>	3.0V-3.6V Single Supply
	<b>Weight</b>	TBD
	<b>Operating Temperature</b>	32° - 158°F (0° - 70°C)
	<b>Current Consumption @ 3.3V</b>	Less than 70 mA peak imaging and scrolling Less than 25 mA hardware finger detection Advanced Power Management
	<b>High-Rate Image Capture</b>	Up to 240 image frames /sec
	<b>ESD Resistance</b>	IEC 61000-4-2 Level 4 (±15KV)
	<b>Detection Matrix</b>	192 x 16 Pixels 9.7 mm x 0.81 mm 500 ppi High-Resolution Images

## NETWORKING/COMMUNICATIONS

<b>Integrated Realtek</b> <b>RTL8151FH-CG</b> <b>10/100/1000 NIC</b>	<b>Ethernet Features</b>	10 Mbit/s operation (10BASE-T; IEEE 802.3i; IEEE 802.3 clauses 13-14) 100 Mbit/s operation (100BASE-TX; IEEE 802.3u; IEEE 802.3 clauses 21-30) 1000 Mbit/s operation (1000BASE-T; IEEE 802.3ab; IEEE 8023 clauses 40) Auto-Negotiation (Automatic Speed Selection) Full Duplex Operation at all Speeds, Half Duplex operation at 10 and 100 Mbit/s IEEE 802.1p QoS (Quality of Service) Support IEEE 802.1q VLAN support IEEE 802.3x Flow Control (IEEE 802.3 clauses 31-32; configurable) IEEE 802.3az EEE (Energy Efficient Ethernet) Jumbo Frame 9K Auto MDI/MDIX Crossover cable detection
	<b>Weight</b>	TBD
	<b>Power Management</b>	ACPI compliant - multiple power modes Situation-sensitive features reduce power consumption Advanced link down power saving for reducing link down power consumption
	<b>Performance Features</b>	TCP/IP/UDP Checksum Offload (configurable) Protocol Offload (ARP & NS) Large send offload and Giant send offload Receiving Side Scaling
	<b>Manageability</b>	Wake-on-LAN from standby and hibernation (Magic Packet and Microsoft

## Technical Specifications

		Wake-Up Frame); Wake-on-LAN from off (Magic Packet only) PXE 2.1 Remote Boot Statistics Gathering (SNMP MIB II, Ethernet-like MIB, Ethernet MIB (802.3x, clause 30)) Comprehensive diagnostic and configuration software suite Virtual Cable Doctor for Ethernet cable status
	<b>Interface</b>	PCI Express 1.1 x1 to fully support ASPM L0s/L1 and CLKREQ
	<b>NIC Device Driver Name</b>	Realtek PCIe GBE Ethernet Family Controller
<b>HP hs3110/3114 HSPA+ Mobile Broadband Module*</b>	<b>Technology/Operating Bands</b>	Modes: WCDMA/HSDPA/HSUPA/HSPA+/AWS/GSM/EDGE/GPRS Penta-band WCDMA/HSDPA/HSUPA/HSPA+/AWS: 850/900/1900/2100/AWS MHz GSM/GPRS/EDGE: 850/900/1800/1900 MHz
	<b>Wireless Protocol Standards</b>	GSM/GPRS/EDGE: Class B, Multi-slot class 33, coding schemes CS1 - CS4 and MSC1 - MSC9. UMTS/WCDMA: Release 99 and Release 7 Advanced Receiver Type 3i
	<b>GPS</b>	GPS Standalone, A-GPS: L1 (Internet- and Network assisted)
	<b>Wireless Parametric Standards</b>	Complies with 3GPP specifications
	<b>Maximum Data Rates</b>	GPRS/EDGE: Multi-slot Class 33, Class B WCDMA PS: UL (384 kbps) / DL (384 kbps) UL/DL HSPA: UL (5.76 Mbps)/ DL (7.2 Mbps) UL/DL HSPA+: UL (5.76 Mbps)/ DL (21Mbps)
	<b>Maximum Output Power</b>	WCDMA/HSPA/HSPA+ 2100/1900/900/850/AWS MHz: +24dBm (Power Class 3) GPRS 1900/1800 MHz: +30dBm (Power Class 1) GPRS 900/850 MHz: +33dBm (Power Class 4) EDGE 1900/1800 MHz: +26dBm (Power Class E2) EDGE 900/850 MHz: +27dBm (Power Class E2)
	<b>Maximum Power Consumption</b>	2500mA (peak); 600mA (average)
	<b>Power Consumption, Sleep Mode</b>	3.6 mA
	<b>Power Management</b>	USB selective suspend, Connected Standby Integrated notebook wireless button
	<b>Antenna Type</b>	Dual high efficiency 5 band antennae with spatial diversity, mounted in the display enclosure
	<b>Form Factor</b>	M.2 Socket 2, USB 2.0 interface high speed
	<b>Weight</b>	<6 g
	<b>Dimensions</b> (Length x Width x Thickness)	2.01 x 1.18 x 0.18 in (42 x 30 x 2.3 mm)
	<b>SIM card supply voltage</b>	1.8 V/3.0 V UICC (SIM/UICC/USIM)
	<b>Voltage, Operating</b>	3.135V~4.4V (3.3 V recommended)

## Technical Specifications

<b>Temperature, Operating</b>	14° to 131° F (-10° to 55° C) (Normal operation) -4° to 158° F (-20° to 70° C) (Extended operation)
<b>Temperature, Storage</b>	-40° to 185° F (-40° to 85° C)
<b>Humidity</b>	5% to 95%
<b>Configuration utilities</b>	HP Connection Manager
<b>LED Activity</b>	LED Off - Radio Off; Solid LED On - Radio On

\* Mobile Broadband is an optional feature sold separately or as an add on feature. Connection requires wireless data service contract, network support, and is not available in all areas. Contact service provider to determine the coverage area and availability. Connection speeds will vary due to location, environment, network conditions, and other factors.

### HP It4112 LTE/HSPA+ Gobi 4G Module\*

<b>Technology/Operating Bands</b>	LTE FDD all bands with diversity: 2100 MHz (Band I), 1900 MHz (Band II), 1800 MHz (Band III), 850 MHz (Band V), 2600 MHz (Band VII), 900 MHz (Band VIII), 800 MHz (Band XX, DD800) WCDMA/HSDPA/HSUPA/HSPA+ all bands with diversity: 2100 MHz (Band I), 1900 MHz (Band II), 800 MHz (Band V), 900 MHz (Band VIII) GSM/GPRS/EDGE: 1900 MHz (Band II), 1800 MHz (Band III), 850 MHz (Band V), 900 MHz (Band VIII)
<b>Wireless Protocol Standards</b>	3GPP Release 8 LTE Specification WCDMA R99, 3GPP Release 5, 6 and 7 UMTS Specification
<b>Wireless Parametric Standards</b>	Complies with 3GPP specifications Release 8 for LTE
<b>Maximum Data Rates</b>	LTE (Category 3): 100 Mbps (Download), 50Mbps (Upload) DC-HSPA+: 42 Mbps (Download), 5.76 Mbps (Upload) HSPA+: 21.6 Mbps (Download), 5.76 Mbps (Upload) EDGE: 236.8 kbps (Download), 236.8 kbps (Upload) GPRS: 85.6 kbps(Download), 85.6 kbps (Upload)
<b>GPS</b>	Standalone
<b>GPS Bands</b>	1575.42 MHz (± 1.023 MHz), GLONASS 1596-1607MHz
<b>Maximum Output Power</b>	LTE: +23 dBm (+/- 2 dBm) WCDMA: +23.5 dBm (+/- 1 dBm) GPRS Band II, III: +29.5 dBm (+/- 1 dBm) GPRS Band V, VIII: +32.5 dBm (+/- 1 dBm) EGPRS Band II, III: +26.5 dBm (+/-1.5 dBm) EGPRS Band V, VIII: +27.5 dBm (+/-1.5 dBm)
<b>Maximum Power Consumption</b>	LTE: 1,200 mA (peak); <900 mA (average) WCDMA: 1,100 mA (peak); <800 mA (average) EGPRS: 2,800 mA (peak); <700 mA (average)
<b>Power Consumption, Sleep Mode</b>	3 mA
<b>Power Management</b>	USB selective suspend, Integrated notebook wireless button
<b>Antenna Type</b>	Dual high efficiency multi-band antennae with spatial diversity
<b>Form Factor</b>	M.2, USB 2.0 interface
<b>Weight</b>	6 g

## Technical Specifications

<b>Dimensions</b> (Length x Width x Thickness)	42 mm × 30 mm × 2.3 mm
<b>Voltage, Operating</b>	3.135 V to 4.4 V (3.3 V +1.1V/-0.165V)
<b>Temperature, operating</b> (from TIA/EIA/IS-98-D)	14° to 131° F (-10° to 55° C)
<b>Temperature, non-operating, 96 hours</b> (from MIL-STD 202 Method 108)	-40° to 185° F (-40° to 85° C)
<b>Humidity, Non-operating</b>	95% relative humidity for 48 hours @ 185° F (85° C) (non-condensing)
<b>LED Activity</b>	LED Off - Radio Off; Solid LED On - Radio On

\* 4G LTE not available on all products, in all regions and only available on products featuring Intel processors. WWAN use requires separately purchased service contract. Check with service provider for coverage and availability in your area. Connection speeds will vary due to location, environment, network conditions, and other factors.

<b>Realtek 802.11 b/g/n (1x1)*</b>	<b>Wireless LAN Standards</b>	IEEE 802.11b IEEE 802.11g IEEE 802.11n
	<b>Interoperability</b>	Wi-Fi certified
	<b>Frequency Band</b>	2.402 - 2.482 GHz
	<b>Data Rates</b>	802.11b: 1, 2, 5.5, 11 Mbps 802.11g: 6, 9, 12, 18, 24, 36, 48, 54 Mbps 802.11n: card will support rates for NSS=1 for RX and TX for 20 MHz channels. Short and long guard interval will be supported.
	<b>Modulation</b>	Direct Sequence Spread Spectrum BPSK, QPSK, CCK, 16-QAM, 64-QAM
	<b>Security<sup>1</sup></b>	IEEE and WiFi compliant 64 / 128 bit WEP encryption for a/b/g mode only AES-CCMP: 128 bit in hardware 802.1x authentication types WPA, WPA2: 802.1x. WPA-PSK, WPA2-PSK, TKIP, and AES. WPA2 certification IEEE 802.11i Cisco Certified Extensions, all versions through V5 WAPI
	<b>Network Architecture Models</b>	Ad-hoc (Peer to Peer) Infrastructure (Access Point Required)
	<b>Roaming</b>	IEEE 802.11 compliant roaming between access points
	<b>Output Power<sup>2</sup></b>	13.5 dBm, nominal
	<b>Power Consumption</b>	Transmit: 2.0 W (max) Receive: 1.6 W (max) Associated to Access Point, Idle: 250 mW nominal Wireless Button Off: 100 mW nominal Radio disabled: 75 mW nominal
	<b>Power Management</b>	ACPI compliant power management 802.11 compliant power saving mode
	<b>Receiver Sensitivity<sup>3</sup></b>	802.11b:-95 dBm (1 Mbps), -93 dBm (2 Mbps), -91 dBm (5.5 Mbps), -88 dBm

## Technical Specifications

	(11 Mbps)
	802.11g: -90 dBm (6 Mbps), -89 dBm (9 Mbps), -87 dBm (12 Mbps), -85 dBm (18 Mbps), -82 dBm (24 Mbps), -79 dBm (36 Mbps), -76 dBm (48 Mbps), -74 dBm (54 Mbps)
	802.11n: -70dBm (72.2 Mbps)
<b>Antenna type</b>	High efficiency antenna with spatial diversity, mounted in the display enclosure
<b>Form Factor</b>	PCI-Express Half-MiniCard
<b>Weight</b>	0.013 lb (6 g)
<b>Dimensions</b>	0.19 x 1.06 x 1.18 in (4.75 x 26.8 x 30 mm)
<b>Operating Voltage</b>	3.3v +/- 9%
<b>Temperature</b>	Operating 14° to 158° F (-10° to 70° C) Non-operating -40° to 176° F (-40° to 80° C)
<b>Humidity</b>	Operating 10% to 90% (non-condensing) Non-operating 5% to 95% (non-condensing)
<b>Altitude</b>	Operating 0 to 10,000 ft (3,048 m) Non-operating 0 to 50,000 ft (15,240 m)
<b>LED Activity</b>	LED Off - Radio OFF; Solid LED On - Radio ON

1. Check latest software/driver release for updates on supported security features.
  2. Maximum output power may vary by country according to local regulations.
  3. Receiver sensitivity is measured at a packet error rate of 8% for 802.11b (CKK modulation) and a packet error rate of 10% for 802.11a/g (OFDM modulation).
- \* Wireless access point and internet service required. Availability of public wireless access points limited.

**Intel Dual Band Wireless-AC 3160 802.11 ac (1x1) WiFi and Bluetooth 4.0 Combo Adaptor\***

<b>General</b>	<b>Dimensions (H x W x D)</b>	Standard: 26.80 mm x 30.00 mm x 2.4 mm Max (Top Side) / 1.35 mm Max (Bottom Side) Low profile: 22 mm x 30.00 mm x 1.5 mm Max (Top Side) / 0.6 mm Max (Bottom Side) NGFF: 22 mm x 30 mm, single sided
	<b>Weight</b>	TBD
	<b>Diversity</b>	No diversity support
	<b>Radio ON/OFF Control</b>	Supported in both hardware and software
	<b>Connector interface</b>	Half Mini Card form factor, based on PCIe electrical interface Next Generation Form Factor, A-SD electrical interface definition support
	<b>LED Output</b>	On/Off
	<b>Operating Temperature (Adapter Shield)</b>	0° to +80° C
	<b>Humidity Non-Operating</b>	50% to 90% RH non-condensing (at temperatures of 25°C to 35°C)
	<b>Operating Systems</b>	Microsoft Windows 7, Microsoft Windows 8, Linux

## Technical Specifications

	<b>Wi-Fi Alliance</b>	Wi-Fi CERTIFIED for 802.11ac, Wi-Fi CERTIFIED a/b/g, Wi-Fi CERTIFIED n, WMM, WPA, WPA2, and WPS, WPS 2.0, Protected Management Frames, Wi-Fi Direct for peer to peer device connections
	<b>Microsoft WHQL</b>	Yes
	<b>IEEE WLAN Standard</b>	IEEE 802.11abgn, 802.11ac, 802.11d, 802.11e, 802.11i, 802.11h, 802.11w
	<b>Architecture</b>	Infrastructure and SoftAP; Supports simultaneous Client and SoftAP modes in 2.4 GHz or 5GHz
	<b>Roaming<sup>1</sup></b>	ACPI and PCI Express compliant power management 802.11 compliant power saving mode
<b>Security</b>	<b>Authentication</b>	WPA and WPA2, 802.1X (EAP-TLS, TTLS, PEAP, LEAP, EAP-FAST), EAP-SIM, EAP-AKA
	<b>Authentication Protocols</b>	PAP, CHAP, TLS, GTC, MS-CHAP, MS-CHAPv2
	<b>Encryption</b>	64-bit and 128-bit WEP, AES-CCMP, TKIP
	<b>Wi-Fi Direct Encryption and Authentication</b>	WPA2, AES-CCMP
	<b>Product Safety</b>	UL, C-UL, CB (IEC 60950-1)
	<b>Management Frame Protection</b>	802.11w (WFA- Protected Management Frames)
<b>Compliance</b>	<b>Retail (Credit Card Processing)</b>	PCI, CISP
	<b>Government</b>	FIPS <sup>2</sup> , FISMA

1. Roaming is supported only within each respective band and mode of access points.

2. Microsoft Windows 7 only.

### HP Integrated Module with Bluetooth 4.0+EDR Wireless Technology

<b>Bluetooth Specification</b>	Dual Mode Bluetooth* 2.1, 2.1+EDR, 3.0, 3.0+HS, 4.0 (BLE)
<b>Dimensions</b>	1.18 x 0.26 x 0.13 in (30 x 6.5 x 3.25 mm)
<b>Frequency Band</b>	2402 to 2480 MHz
<b>Number of Available Channels</b>	79 (1 MHz) available channels
<b>Data Rates and Throughput</b>	3 Mbps data rate; throughput up to 2.17 Mbps Synchronous Connection Oriented links up to 3, 64 kbps, voice channels Asynchronous Connection Less links 2178.1 kbps/177.1 kbps asymmetric or 1306.9 kbps symmetric
<b>Transmit Power</b>	-1.5 dBm to 4 dBm (Bluetooth Class II)
<b>Receiver Sensitivity</b>	Better than -20 dBm at 0.1 % raw bit error rate
<b>Power Consumption</b>	Peak (Tx) 264 mW Peak (Rx) 231 mW Sleep <1 mW
<b>Antenna</b>	Internally integrated within module
<b>Range</b>	Up to 33 ft (10 m)



## Technical Specifications

<b>Electrical Interface</b>	USB 2.0 compliant Microsoft Windows Plug and Play compliant
<b>Bluetooth Software Supported</b>	Broadcom Bluetooth for Windows Microsoft Windows Bluetooth Software
<b>Link Topology</b>	Point to Point, Multipoint Pico Nets up to 7 slaves
<b>Security</b>	Full support of Bluetooth Security Provisions
<b>Power Management</b>	Microsoft Windows ACPI, and USB Bus Support Self configurable to optimize power conservation in all operating modes, including Standby, Hold, Park, and Sniff
<b>Certifications</b>	All necessary regulatory approvals for supported countries, including: FCC (47 CFR) Part 15C, Section 15.247 & 15.249 ETS 300 328, ETS 300 826 Low Voltage Directive IEC950 UL, CSA, and CE Mark
<b>Temperature</b>	Operating -14° to 158° F (-10° to 70° C) Non-operating -40° to 212° F (-40° to 100° C)
<b>Humidity</b>	Operating 0% to 90% Non-operating 0% to 95%
<b>Altitude</b>	Operating 15,000 ft (4,572 m) Non-operating 40,000 ft (12,192 m)
<b>Bluetooth Profiles Supported</b>	Serial Port Profile (SPP) <sup>1</sup> Service Discovery Application Profile (SDAP) Dial-Up Networking (DUN) <sup>1,2</sup> Generic Object Exchange Profile (GOEP) <sup>1,2</sup> Object Push Profile (OPP) <sup>1,2</sup> File Transfer Profile (FTP) Synchronization Profile (SYNC) Hard Copy Cable Replacement (HCRP) <sup>1,2</sup> Personal Area Networking Profile (PAN) <sup>1,2</sup> Human Interface Device Profile (HID) <sup>1,2</sup> FAX Profile (FAX) Basic Imaging Profile (BIP) <sup>2</sup> Headset Profile (HSP) Hands Free Profile (HFP) Advanced Audio Distribution Profile (A2DP)

1. indicates the profile is supported by Microsoft Windows XP SP2

2. indicates the profile is part of Windows Vista

\* Wireless access point and internet service required. Availability of public wireless access points limited. The specifications for the 802.11ac WLAN are draft specifications and are not final. If the final specifications differ from the draft specifications, it may affect the ability of the notebook to communicate with other 802.11ac WLAN devices.

<b>Intel Dual Band Wireless- N 7260 802.11 a/b/g/n (2x2) WiFi + Bluetooth 4.0 Combo Adaptor*</b>	<b>Wireless LAN Standards</b>	IEEE 802.11a IEEE 802.11b IEEE 802.11g IEEE 802.11n
--	-------------------------------	--

## Technical Specifications

<b>Interoperability</b>	Wi-Fi certified Cisco Compatible Extensions Program compliant with Microsoft Windows 7, Windows Vista and XP (details at: <a href="http://www.hp.com/go/notebooks/WLAN">http://www.hp.com/go/notebooks/WLAN</a> )
<b>Frequency Band</b>	802.11b/g/n 2.402 - 2.482 GHz 802.11a/n 4.9 - 4.95 GHz (Japan) 5.15 - 5.25 GHz 5.25 - 5.35 GHz 5.47 - 5.725 GHz 5.825 - 5.850 GHz
<b>Antenna Structure</b>	2 transmit; 2 receive (2x2)
<b>Data Rates</b>	802.11a: 6, 9, 12, 18, 24, 36, 48, 54 Mbps 802.11b: 1, 2, 5.5, 11 Mbps 802.11g: 6, 9, 12, 18, 24, 36, 48, 54 Mbps 802.11n: card will support rates for NSS=1 and NSS=2 for RX and TX for 20 and 40 MHz channels. Short and long guard interval shall be supported.
<b>Modulation</b>	Direct Sequence Spread Spectrum CCK, BPSK, QPSK, 16-QAM, 64-QAM
<b>Security<sup>1</sup></b>	<ul style="list-style-type: none"><li>● IEEE and WiFi compliant 64 / 128 bit WEP encryption for a/b/g mode only</li><li>● AES-CCMP: 128 bit in hardware</li><li>● 802.1x authentication</li><li>● WPA, WPA2: 802.1x. WPA-PSK, WPA2-PSK, TKIP, and AES.</li><li>● WPA2 certification</li><li>● IEEE 802.11i</li><li>● Cisco Certified Extensions, all versions through V5</li><li>● WAPI</li></ul>
<b>Sub-channels</b>	Multinational support with frequency bands and channels compliant to local regulations.
<b>Network Architecture Models</b>	Ad-hoc (Peer to Peer) Infrastructure (Access Point Required)
<b>Roaming</b>	IEEE 802.11 compliant roaming between band Access Points
<b>Output Power<sup>2</sup></b>	<ul style="list-style-type: none"><li>● 2.4G: +13.5dBm minimum</li><li>● 5G: +12dBm minimum</li></ul>
<b>Power Consumption</b>	Transmit: 2.0 Watts Receive: 1.6 Watts Idle mode <sup>3</sup> : 250 mW (WLAN Associated) Idle mode: 100 mW (WLAN unassociated) Radio off: 75 mW
<b>Power Management</b>	ACPI and PCI Express compliant power management 802.11 compliant power saving mode
<b>Receiver Sensitivity<sup>4</sup></b>	802.11g: -90 dBm (6 Mbps), -89 dBm (9 Mbps), -87 dBm (12 Mbps), -85 dBm (18 Mbps), -82 dBm (24 Mbps), -79 dBm (36 Mbps), -76 dBm (48 Mbps), -74 dBm (54 Mbps)  802.11b: -95 dBm (1 Mbps), -93 dBm (2 Mbps), -91 dBm (5.5 Mbps), -88 dBm (11 Mbps)

## Technical Specifications

	802.11g:-90 dBm (6 Mbps), -89 dBm (9 Mbps), -87 dBm (12 Mbps), -85 dBm (18 Mbps), -82 dBm (24 Mbps), -79 dBm (36 Mbps), -76 dBm (48 Mbps), -74 dBm (54 Mbps)
	802.11n:-69 dBm (150 Mbps), -66 dBm (300 Mbps)
<b>Antenna Connections</b>	2 U.FL type connectors (output impedance of 50 ± 2 ohms)
<b>Form Factor</b>	PCI-Express Half-MiniCard
<b>Dimensions</b>	0.12 x 1.06 x 1.18 in (3.1 x 26.8 x 30.0 mm)
<b>Weight</b>	TBD
<b>Operating Voltage</b>	3.3v +/- 9%
<b>Temperature</b>	Operating 14° to 158° F (-10° to 70° C) Non-operating -40° to 176° F (-40° to 80° C)
<b>Humidity</b>	Operating 10% to 90% (non-condensing) Non-operating 5% to 95% (non-condensing)
<b>Altitude</b>	Operating 0 to 10,000 ft (3,048 m) Non-operating 0 to 50,000 ft (15,240 m)
<b>LED Activity</b>	LED Off - Radio OFF; Solid LED On - Radio ON
	<ol style="list-style-type: none"><li>1. Check latest software/driver release for updates on supported security features.</li><li>2. Maximum output power may vary by country according to local regulations.</li><li>3. In Power Save Polling mode and on battery power.</li><li>4. Receiver sensitivity is measured at a packet error rate of 8% for 802.11b (CCK modulation) and a packet error rate of 10% for 802.11a/g (OFDM modulation).</li><li>5. WLAN supplier's client utility is required for Cisco Compatible Extensions support with Microsoft Windows XP. WLAN may also be compatible with certain third-party software supplicants. WLAN supplier IHV extensions required for Cisco Compatible Extensions support for Microsoft Windows Vista.</li></ol>
<b>HP Integrated Module with Bluetooth 4.0+EDR Wireless Technology</b>	
<b>Bluetooth Specification</b>	4.0+EDR Compliant
<b>Dimensions</b>	1.18 x 0.26 x 0.13 in (30 x 6.5 x 3.25 mm)
<b>Frequency Band</b>	2402 to 2480 MHz
<b>Number of Available Channels</b>	79 (1 MHz) available channels
<b>Data Rates and Throughput</b>	3 Mbps data rate; throughput up to 2.17 Mbps Synchronous Connection Oriented links up to 3, 64 kbps, voice channels Asynchronous Connection Less links 2178.1 kbps/177.1 kbps asymmetric or 1306.9 kbps symmetric
<b>Transmit Power</b>	-1.5 dBm to 4 dBm (Bluetooth Class II)
<b>Receiver Sensitivity</b>	Better than -20 dBm at 0.1 % raw bit error rate
<b>Power Consumption</b>	Peak (Tx) 264 mW Peak (Rx) 231 mW Sleep <1 mW
<b>Antenna</b>	Internally integrated within module
<b>Range</b>	Up to 33 ft (10 m)
<b>Electrical Interface</b>	USB 2.0 compliant Microsoft Windows Plug and Play compliant

## Technical Specifications

<b>Bluetooth Software Supported</b>	Broadcom Bluetooth for Windows Microsoft Windows Bluetooth Software
<b>Link Topology</b>	Point to Point, Multipoint Pico Nets up to 7 slaves
<b>Security</b>	Full support of Bluetooth Security Provisions
<b>Power Management</b>	Microsoft Windows ACPI, and USB Bus Support Self configurable to optimize power conservation in all operating modes, including Standby, Hold, Park, and Sniff
<b>Certifications</b>	All necessary regulatory approvals for supported countries, including: FCC (47 CFR) Part 15C, Section 15.247 & 15.249 ETS 300 328, ETS 300 826 Low Voltage Directive IEC950 UL, CSA, and CE Mark
<b>Bluetooth Profiles Supported</b>	Serial Port Profile (SPP) <sup>1</sup> Service Discovery Application Profile (SDAP) Dial-Up Networking (DUN) <sup>1,2</sup> Generic Object Exchange Profile (GOEP) <sup>1,2</sup> Object Push Profile (OPP) <sup>1,2</sup> File Transfer Profile (FTP) Synchronization Profile (SYNC) Hard Copy Cable Replacement (HCRP) <sup>1,2</sup> Personal Area Networking Profile (PAN) <sup>1,2</sup> Human Interface Device Profile (HID) <sup>1,2</sup> FAX Profile (FAX) Basic Imaging Profile (BIP) <sup>2</sup> Headset Profile (HSP) Hands Free Profile (HFP) Advanced Audio Distribution Profile (A2DP)

1. indicates the profile is supported by Microsoft Windows XP SP2

2. indicates the profile is part of Windows Vista

\* Wireless access point and internet service required. Availability of public wireless access points limited.

## AUDIO/MULTIMEDIA - DTS SOUND+

<b>Hardware</b>	<b>Implementation</b>	IDT 92HD91
	<b>Function Key</b>	Volume up, volume down, and mute
	<b>Volume Controls</b>	
	<b>Full Duplex</b>	Yes
	<b>Microphone In</b>	Stereo
	<b>Headphone/Line Out</b>	Stereo
	<b>Integrated Microphone</b>	Yes, dual digital microphone array when equipped with optional webcam

## Technical Specifications

<b>Audio Output Quality</b>	<b>Frequency Response</b>	20 Hz - 20 kHz
	<b>Signal to Noise Ratio</b>	>85 dB
	<b>Total Harmonic Distortion</b>	0.01%
	<b>Noise Floor</b>	-110 dB
	<b>Play/Record Sampling Rate(s)</b>	8 kHz - 48kHz
	<b>DAC</b>	16, 20 or 24-bit
	<b>ADC</b>	16 or 20-bit

<b>Integrated Stereo Speakers</b>	<b>Power Rating</b>	2 Watts
	<b>Impedance</b>	4 Ohms

## POWER

<b>HP 90W Smart AC Adapter (discrete configurations)</b>	<b>Dimensions</b>	5.00 x 1.97 x 1.1 in (12.7 x 5.0 x 2.9 cm)	
	<b>Weight</b>	0.82 lb (370 g)	
	<b>Input</b>	<b>Input</b>	100 to 240 VAC
		<b>Input Efficiency</b>	87% min at 115 VAC
		<b>Input frequency range</b>	47 to 63 Hz
	<b>Output</b>	<b>Input AC current</b>	1.5 A at 90 VAC, 0.75 A at 180 VAC PFC Version 2.4 A at 90 VAC, 1.2 A at 180 VAC NON PFC Version
		<b>Output power</b>	90W
		<b>DC output</b>	19.0V
		<b>Hold-up time</b>	5 msec at 115 VAC input
		<b>Output current limit</b>	<11A, Over voltage protection- 29V max automatic shutdown
	<b>Connector</b>	3 pin/grounded, mates with interchangeable cords	
	<b>Environmental Design</b>	<b>Operating temperature</b>	32° to 104° F (0° to 40° C)
		<b>Non-operating (storage) temperature</b>	-4° to 149° F (-20° to 65° C)
<b>Altitude</b>		0 to 10,000 ft (0 to 3,048 m)	
<b>Humidity</b>		20% to 80%	
<b>EMI and Safety Certifications</b>	<b>Storage Humidity</b>	10% to 90%	
		CE Mark - full compliance with LVD and EMC directives; Worldwide safety standards - IEC60950, EN60950, UL60950, Class1, SELV; Agency approvals - C-UL-US, NORDICS, DENAN, EN55022 Class B, FCC Class B, CISPR22 Class B, CCC, NOM-1 NYCE; MTBF- over 200,000 hours at 25°C ambient condition.	

## Technical Specifications

<b>HP 65W Smart AC Adapter (Configurations with integrated graphics)</b>	<b>Dimensions</b>	4.17 x 1.85 x 1.1 in (10.6 x 4.7 x 2.8 cm)	
	<b>Weight</b>	0.62 lb (280 g)	
	<b>Input</b>	<b>Input</b>	100 to 240 VAC
		<b>Input Efficiency</b>	87% min at 115 VAC
	<b>Output</b>	<b>Input frequency range</b>	47 to 63 Hz
		<b>Input AC current</b>	1.7 A at 90 VAC, 0.85 A at 180 VAC
		<b>Output power</b>	65W
		<b>DC output</b>	18.5V
		<b>Hold-up time</b>	5 msec at 115 VAC input
		<b>Output current limit</b>	<11A, Over voltage protection- 29V max automatic shutdown
		<b>Connector</b>	3 pin/grounded, mates with interchangeable cords
	<b>Environmental Design</b>	<b>Operating temperature</b>	32° to 104° F (0° to 40° C)
		<b>Non-operating (storage) temperature</b>	-4° to 149° F (-20° to 65° C)
		<b>Altitude</b>	0 to 10,000 ft (0 to 3,048 m)
		<b>Humidity</b>	20% to 80%
<b>Storage Humidity</b>		10% to 90%	
<b>EMI and Safety Certifications</b>	CE Mark - full compliance with LVD and EMC directives; Worldwide safety standards - IEC60950, EN60950, UL60950, Class1, SELV; Agency approvals - C-UL-US, NORDICS, DENAN, EN55022 Class B, FCC Class B, CISPR22 Class B, CCC, NOM-1 NYCE; MTBF - over 200,000 hours at 25°C ambient condition.		
<b>9-Cell (93 WHr) Lithium-Ion battery</b>	<b>Dimensions (H x W x L)</b>	1.57 x 1.85 x 10.59 in (4.0 x 4.7 x 26.9 cm)	
	<b>Weight (max)</b>	1.07 lb (0.488 kg)	
	<b>Cells/Type</b>	9-cell Lithium-Ion	
	<b>Energy</b>	<b>Watt-hour Capacity</b>	93 WHr
		<b>Amp-hour capacity</b>	8.4Ah
		<b>Watt-hour capacity</b>	11.1V
	<b>Temperature</b>	<b>Operating (Charging)</b>	32° to 113° F (0° to 45° C)
		<b>Operating (Discharging)</b>	14° to 140° F (-10° to 60° C)
		<b>Non-operating</b>	-4° to 140° F (-20° to 60° C)
	<b>Battery Re-Charge Time</b>	<b>System in OFF or Standby Mode</b>	3 to 4 hours
<b>System ON</b>		4 to 6 hours (depending on system power consumption)	

## Technical Specifications

<b>6-Cell (47 WHr) Lithium-Ion battery</b>	<b>Dimensions (H x W x L)</b>	0.85 x 1.76 x 10.59 in (2.16 x 4.46 x 26.9 cm)	
	<b>Weight (max)</b>	0.70lb, (0.312kg)	
	<b>Cells/Type</b>	6-cell Lithium-Ion	
	<b>Energy</b>	<b>Watt-hour Capacity</b>	10.8V
		<b>Amp-hour capacity</b>	4.4Ah
		<b>Watt-hour capacity</b>	47Wh
	<b>Temperature</b>	<b>Operating (Charging)</b>	32° to 113° F (0° to 45° C)
		<b>Operating (Discharging)</b>	14° to 122° F (-10° to 50° C)
		<b>Non-operating</b>	-4° to 122° F (-20° to 50° C)
	<b>Battery Re-Charge Time</b>	<b>System in OFF or Standby Mode</b>	2.5 hours
		<b>System ON</b>	3 to 5 hours
		<b>Fuel Gauge LED</b>	No
	<b>Warranty</b>	1 year	
	<b>Optional Travel Battery Available</b>	No	

## ENVIRONMENTAL

### Environmental Data

#### Eco-Label Certifications & Declarations

This product has received or is in the process of being certified to the following approvals and may be labeled with one or more of these marks:

- IT ECO declaration
- US ENERGY STAR®
- EPEAT <Gold> registered in the United States. See <http://www.epeat.net> for registration status in your country.

### HP ProBook 440 G1 Notebook PC

#### System Configuration

The configuration used for the Energy Consumption and Declared Noise Emissions data for the Notebook model is based on a "Typically Configured Notebook".

#### Energy Consumption

(in accordance with US ENERGY STAR® test method)

	115VAC, 60Hz	230VAC, 50Hz	100VAC, 60Hz
Normal Operation	6.21 W	6.30 W	6.08 W
Sleep	0.79 W	0.85 W	0.80 W
Off	0.39 W	0.45 W	0.39 W

#### NOTE:

Energy efficiency data listed is for an ENERGY STAR® compliant product if offered within the model family. HP computers marked with the ENERGY STAR® Logo are compliant with the applicable U.S. Environmental Protection Agency (EPA) ENERGY STAR® specifications for computers. If a model family does not offer ENERGY STAR® compliant configurations, then energy efficiency data listed is

## Technical Specifications

for a typically configured PC featuring a hard disk drive, a high efficiency power supply, and a Microsoft Windows® operating system.

Heat Dissipation*	115VAC, 60Hz	230VAC, 50Hz	100VAC, 60Hz
Normal Operation	21 BTU/hr	22 BTU/hr	21 BTU/hr
Sleep	3 BTU/hr	3 BTU/hr	3 BTU/hr
Off	1 BTU/hr	2 BTU/hr	1 BTU/hr

\* Heat dissipation is calculated based on the measured watts, assuming the service level is attained for one hour.

### Declared Noise Emissions (in accordance with ISO 7779 and ISO 9296)

	Sound Power (LWAd, bels)	Sound Pressure (LpAm, decibels)
Typically Configured - Idle	3.2	29
Fixed Disk - Random writes	3.2	29

### Batteries

This battery(s) in this product comply with EU Directive 2006/66/EC

Batteries used in the product do not contain:

- Mercury greater than 1ppm by weight
- Cadmium greater than 20ppm by weight

Battery size: CR2032 (coin cell)

Battery type: Lithium

Battery size: 6-cell high capacity Lithium-Ion battery (optional 8 cell available)

Battery type:

### Additional Information

- This product is in compliance with the Restrictions of Hazardous Substances (RoHS) directive - 2011/65/EC.
- This HP product is designed to comply with the Waste Electrical and Electronic Equipment (WEEE) Directive - 2002/96/EC.
- This product is in compliance with California Proposition 65 (State of California; Safe Drinking Water and Toxic Enforcement Act of 1986).
- This product is in compliance with the IEEE 1680 (EPEAT) standard at the <gold> level, see [www.epeat.net](http://www.epeat.net)
- Plastics parts weighing over 25 grams used in the product are marked per ISO11469 and ISO1043.
- This product contains 0% post-consumer recycled plastic (by wt.)
- This product is 95.78% recycle-able when properly disposed of at end of life.

### Packaging Materials

- External:
  - PAPER/Cardboard & misc 325 g
  - PAPER/Corrugated 51 g
- Internal:
  - PLASTIC/EPE-Expanded Polyethylene 68 g
  - PLASTIC/Polyethylene low density 15 g
  - PLASTIC/PET 20 g
  - OTHER/OTHER 20 g
- The PAPER/Cardboard & misc packaging material is made from 40 % recycled content.
- The PAPER/Corrugated packaging material is made from 40 % recycled content.



## Technical Specifications

- The PLASTIC/EPE-Expanded Polyethylene packaging is made from 40 % recycled content.
- The PLASTIC/Polyethylene low density packaging is made from 40 % recycled content.
- The PLASTIC/PET packaging is made from 40 % recycled content.
- The OTHER/OTHER packaging is made from 40 % recycled content.

### HP ProBook 450 G1 Notebook PC

#### System Configuration

The configuration used for the Energy Consumption and Declared Noise Emissions data for the Notebook model is based on a "Typically Configured Notebook".

#### Energy Consumption

(in accordance with US ENERGY

STAR® test method)

	115VAC, 60Hz	230VAC, 50Hz	100VAC, 60Hz
Normal Operation	8.86 W	9.30 W	8.97 W
Sleep	0.48 W	0.56 W	0.46 W
Off	0.33 W	0.43 W	0.33 W

#### NOTE:

Energy efficiency data listed is for an ENERGY STAR® compliant product if offered within the model family. HP computers marked with the ENERGY STAR® Logo are compliant with the applicable U.S. Environmental Protection Agency (EPA) ENERGY STAR® specifications for computers. If a model family does not offer ENERGY STAR® compliant configurations, then energy efficiency data listed is for a typically configured PC featuring a hard disk drive, a high efficiency power supply, and a Microsoft Windows® operating system.

#### Heat Dissipation\*

	115VAC, 60Hz	230VAC, 50Hz	100VAC, 60Hz
Normal Operation	30 BTU/hr	32 BTU/hr	31 BTU/hr
Sleep	2 BTU/hr	2 BTU/hr	2 BTU/hr
Off	1 BTU/hr	1 BTU/hr	1 BTU/hr

\* Heat dissipation is calculated based on the measured watts, assuming the service level is attained for one hour.

#### Declared Noise Emissions

(in accordance with

ISO 7779 and ISO 9296)

	Sound Power (LWAd, bels)	Sound Pressure (LpAm, decibels)
Typically Configured - Idle	3.2	27
Fixed Disk - Random writes	3.2	27

#### Batteries

This battery(s) in this product comply with EU Directive 2006/66/EC

Batteries used in the product do not contain:

- Mercury greater than 1ppm by weight
- Cadmium greater than 20ppm by weight

Battery size: CR2032 (coin cell)

Battery type: Lithium

Battery size: 6-cell high capacity Lithium-Ion battery (optional 8 cell available)

Battery type:

#### Additional Information

- This product is in compliance with the Restrictions of Hazardous Substances (RoHS) directive - 2011/65/EC.
- This HP product is designed to comply with the Waste Electrical and Electronic Equipment (WEEE) Directive - 2002/96/EC.
- This product is in compliance with California Proposition 65 (State of California; Safe Drinking

## Technical Specifications

- Water and Toxic Enforcement Act of 1986).
- This product is in compliance with the IEEE 1680 (EPEAT) standard at the <gold> level, see [www.epeat.net](http://www.epeat.net)
- Plastics parts weighing over 25 grams used in the product are marked per ISO11469 and ISO1043.
- This product contains 0% post-consumer recycled plastic (by wt.)
- This product is 96.08% recycle-able when properly disposed of at end of life.

### Packaging Materials

- External:
  - PAPER/Corrugated 560.5 g
- Internal:
  - PLASTIC/EPE-Expanded Polyethylene 37 g
  - PLASTIC/Polyethylene low density 24 g
  - PLASTIC/PET 2.5 g
  - OTHER/OTHER 20 g
- The PAPER/Corrugated packaging material is made from 40 % recycled content.
- The PLASTIC/EPE-Expanded Polyethylene packaging is made from 40 % recycled content.
- The PLASTIC/Polyethylene low density packaging is made from 40 % recycled content.
- The PLASTIC/PET packaging is made from 40 % recycled content.
- The OTHER/OTHER packaging is made from 40 % recycled content.

## HP ProBook 470 G1 Notebook PC

### System Configuration

The configuration used for the Energy Consumption and Declared Noise Emissions data for the Notebook model is based on a "Typically Configured Notebook".

### Energy Consumption

(in accordance with US ENERGY STAR® test method)

	115VAC, 60Hz	230VAC, 50Hz	100VAC, 60Hz
Normal Operation	8.49 W	8.91 W	8.84 W
Sleep	0.48 W	0.57 W	0.46 W
Off	0.33 W	0.42 W	0.33 W

### NOTE:

Energy efficiency data listed is for an ENERGY STAR® compliant product if offered within the model family . HP computers marked with the ENERGY STAR® Logo are compliant with the applicable U.S. Environmental Protection Agency (EPA) ENERGY STAR® specifications for computers. If a model family does not offer ENERGY STAR® compliant configurations, then energy efficiency data listed is for a typically configured PC featuring a hard disk drive, a high efficiency power supply, and a Microsoft Windows® operating system.

### Heat Dissipation\*

	115VAC, 60Hz	230VAC, 50Hz	100VAC, 60Hz
Normal Operation	29 BTU/hr	30 BTU/hr	30 BTU/hr
Sleep	2 BTU/hr	2 BTU/hr	2 BTU/hr
Off	1 BTU/hr	1 BTU/hr	1 BTU/hr

\*NOTE: Heat dissipation is calculated based on the measured watts, assuming the service level is attained for one hour.

## Technical Specifications

### Declared Noise Emissions (in accordance with ISO 7779 and ISO 9296)

	Sound Power (LWAd, bels)	Sound Pressure (LpAm, decibels)
Typically Configured - Idle	3.2	29
Fixed Disk - Random writes	3.2	29

### Batteries

This battery(s) in this product comply with EU Directive 2006/66/EC

Batteries used in the product do not contain:

- Mercury greater than 1ppm by weight
- Cadmium greater than 20ppm by weight

Battery size: CR2032 (coin cell)

Battery type: Lithium

Battery size: 6-cell high capacity Lithium-Ion battery (optional 8 cell available)

Battery type:

### Additional Information

- This product is in compliance with the Restrictions of Hazardous Substances (RoHS) directive - 2011/65/EC.
- This HP product is designed to comply with the Waste Electrical and Electronic Equipment (WEEE) Directive - 2002/96/EC.
- This product is in compliance with California Proposition 65 (State of California; Safe Drinking Water and Toxic Enforcement Act of 1986).
- This product is in compliance with the IEEE 1680 (EPEAT) standard at the <gold> level, see [www.epeat.net](http://www.epeat.net)
- Plastics parts weighing over 25 grams used in the product are marked per ISO11469 and ISO1043.
- This product contains 0% post-consumer recycled plastic (by wt.)
- This product is 96.08% recycle-able when properly disposed of at end of life.

### Packaging Materials

- External:
  - PAPER/Cardboard & misc 481 g
- Internal:
  - PLASTIC/EPE-Expanded Polyethylene 55 g
  - PLASTIC/Polyethylene low density 26 g
  - PLASTIC/PET 3 g
  - OTHER/OTHER 20 g
- The PAPER/Cardboard & misc packaging material is made from 40 % recycled content.
- The PLASTIC/EPE-Expanded Polyethylene packaging is made from 40 % recycled content.
- The PLASTIC/Polyethylene low density packaging is made from 40 % recycled content.
- The PLASTIC/PET packaging is made from 40 % recycled content.
- The OTHER/OTHER packaging is made from 40 % recycled content.

## ALL MODELS

### MATERIAL USAGE

This product does not contain any of the following substances in excess of regulatory limits (for reference of these limits please refer to the HP General Specification of the Environment

([http://www.hp.com/hpinfo/globalcitizenship/environment/supplychain/gen\\_specifications.html](http://www.hp.com/hpinfo/globalcitizenship/environment/supplychain/gen_specifications.html)):

## Technical Specifications

- Asbestos
- Certain Azo Colorants
- Certain Brominated Flame Retardants – may not be used as flame retardants in plastics
- Cadmium
- Chlorinated Hydrocarbons
- Chlorinated Paraffins
- Formaldehyde
- Halogenated Diphenyl Methanes
- Lead carbonates and sulfates
- Lead and Lead compounds
- Mercuric Oxide Batteries
- Ozone Depleting Substances
- Polybrominated Biphenyls (PBBs)
- Polybrominated Biphenyl Ethers (PBBEs)
- Polybrominated Biphenyl Oxides (PBBOs)
- Polychlorinated Biphenyl (PCB)
- Polychlorinated Terphenyls (PCT)
- Polyvinyl Chloride (PVC) – except for wires and cables, and certain retail packaging has been voluntarily removed from most applications.
- Radioactive Substances
- Tributyl Tin (TBT), Triphenyl Tin (TPT), Tributyl Tin Oxide (TBT0)
- Nickel finishes that release greater than 0.5 µgrams/cm<sup>2</sup>/week, measured according to EN 1811:1998, are not used on any product surface designed to be frequently handled or touched by users.

## END-OF-LIFE MANAGEMENT AND RECYCLING

Hewlett-Packard offers end-of-life HP product return and recycling programs in many geographic areas. To recycle your product, please go to: <http://www.hp.com/go/reuse-recycle> or contact your nearest HP sales office. Products returned to HP will be recycled, recovered or disposed of in a responsible manner.

The EU WEEE directive (2002/95/EC) requires manufacturers to provide treatment information for each product type for use by treatment facilities. This information (product disassembly instructions) is posted on the Hewlett Packard web site at: <http://www.hp.com/go/recyclers>. These instructions may be used by recyclers and other WEEE treatment facilities as well as HP OEM customers who integrate and re-sell HP equipment.

## HEWLETT-PACKARD CORPORATE ENVIRONMENTAL INFORMATION

For more information about HP's commitment to the environment:

Global Citizenship Report

<http://www.hp.com/hpinfo/globalcitizenship/gcreport/index.html>

Environment website

<http://www.hp.com/environment>

Eco-label certifications

<http://www.hp.com/hpinfo/globalcitizenship/environment/productdesign/ecolabels.html>

ISO 14001 certificates:

<http://www.hp.com/hpinfo/globalcitizenship/environment/operations/envmanagement.html>

# QuickSpecs

---

**HP ProBook 440 G1 Notebook PC**  
**HP ProBook 450 G1 Notebook PC**  
**HP ProBook 470 G1 Notebook PC**

Technical Specifications

## **Country of Origin**

China



# QuickSpecs

HP ProBook 440 G1 Notebook PC

HP ProBook 450 G1 Notebook PC

HP ProBook 470 G1 Notebook PC

Options and Accessories (sold separately and availability may vary by country)

Type	Description	Part #
<b>Cases</b>	HP Business Nylon Case	H5M92AA
	HP Business 4 Wheel Roller Case	H5M93AA
	HP Business Backpack (up to 17.3")	H5M90AA
<b>Docking</b>	HP LCD Monitor Stand	QM196AA
	HP Dual Hinge Notebook Stand	AW661AA#xxx
	HP USB 2.0 Port Replicator	H1L07AA#xxx
	HP USB 3.0 Port Replicator	H1L08AA#xxx
<b>Input/Output - Mice</b>	HP Wireless Mobile Mouse	H2L63AA
	HP X4000b Bluetooth Mouse	H3T50AA#xxx
<b>Input/Output - Keyboards</b>	HP USB Essential Keyboard/Mouse	H6L29AA
	HP Stylish Wireless KB/Mouse	H4B79AA
<b>Memory</b>	HP 2GB DDR3L-1600 1.35V SODIMM	H6Y73AA#XXX
	HP 4GB DDR3L-1600 1.35V SODIMM	H6Y75AA#XXX
	HP 8GB DDR3L-1600 1.35V SODIMM	H6Y77AA#XXX
<b>Adapters</b>	90W Slim Combo Adapter	H4A41AA#xxx
	90W w/USB Universal Adapter	H4A43AA#ABA
	90W Smart Auto/Truck Adapter	ED493AA
	HP 65W Slim Adapter	AX727AA#XXX
<b>Security</b>	HP Notebook Combo Lock	AY475AA#XXX
	HP UltraSlim Keyed Cable Lock	H4D73AA
<b>Storage - External Storage</b>	HP Mobile USB DVDRW Non-LS	A2U57AA
<b>Health and Education</b>	HP EliteDisplay E271i 27-inch IPS LED Monitor	D7Z72AA/A8/AS/AT
	HP EliteDisplay E231 23-inch LED Monitor	C9V75AA/A8/AS/AT
	HP EliteDisplay E201 20-inch LED Monitor	C9V73AA/A8/AS/AT
	HP ProDisplay P221 21.5" LED Monitor	C9E49AA/A8/AS/AT
	HP ProDisplay P201 20" LED Monitor	C9F26AA/A8/AS/AT



## Options and Accessories (sold separately and availability may vary by country)

Copyright © 2014 Hewlett-Packard Development Company, L.P.

Intel, Core, and Celeron are registered trademarks or trademarks of Intel Corporation in the U.S. and/or other countries. Microsoft and Windows are U.S. registered trademarks of Microsoft Corporation. Adobe is a trademark of Adobe Systems Incorporated. Bluetooth is a trademark owned by its proprietor and used by Hewlett-Packard Company under license. ENERGY STAR is a registered mark owned by the U.S. government.

The information contained herein is subject to change without notice and is provided "as is" without warranty of any kind. The warranties for HP products are set forth in the express limited warranty statements accompanying such products. Nothing herein should be construed as constituting an additional warranty. HP shall not be liable for technical or editorial errors or omissions contained herein.